


# FANS & AIR CONDITIONERS


## EXHAUST FANS & PANEL FANS

### WALL EXHAUST FAN

- Sturdily constructed, direct drive, horizontal discharge for industrial, commercial and farm applications
- Constructed from all-aluminum extrusions
- Heavy-duty OSHA motor mount/guard
- Ball-bearing with overload protection
- Aluminum shutters automatically open when fan starts and close when fan stops
- Complete with aluminum shutters



Exhaust Fan



### EXHAUST SERIES

The Exhaust series comes equipped with aluminum louvres which opens automatically when fan is operating.



### EXHAUST


Model No.	Dimensions			RPM	HP	CFM
	A"	B"	C"			
<b>STANDARD</b>						
<b>FREE AIR</b>						

BA129	17	14	6 3/4	11 1/2	1725	1/4	1450
BA132	18 3/4	15 3/4	6 3/4	11 1/2	1725	1/4	2200
BA135	20 3/4	17 3/4	6 3/4	11 1/2	1725	1/4	3300
BA138	22 3/4	19 3/4	6 3/4	11 1/2	1725	1/4	4300
BA141	24 3/4	21 3/4	6 3/4	12 1/4	1725	1/3	5000

<b>2-SPEED</b>		<b>FREE AIR</b>					
BA130	17	14	6 3/4	11 1/2	1725/1140	1/4	1450/1000
BA133	18 3/4	15 3/4	6 3/4	11 1/2	1725/1140	1/4	2200/1450
BA136	20 3/4	17 3/4	6 3/4	11 1/2	1725/1140	1/4	3300/2100
BA139	22 3/4	19 3/4	6 3/4	11 1/2	1725/1140	1/4	4300/2850
BA142	24 3/4	21 3/4	6 3/4	12 1/4	1725/1140	1/3	5000/3250
BA495	28 3/4	25 3/4	6 3/4	12 1/4	1100/800	1/3	5000/3000

### PANEL FANS

- Sturdily constructed, direct drive, horizontal discharge for industrial, commercial and farm applications
- Motors are totally enclosed, continuous run, fan duty with built-in automatic overload protection
- Ball bearing motors for easy maintenance
- 120 V, other voltages available on request
- Baked enamel finish



### PANEL SERIES

Used when moving air within an enclosed area

### PANEL

Fan Dia."	Model No.	Dimensions	
		A"	B"
<b>STANDARD</b>			
12	BA059	17	11 1/2
14	BA062	18 3/4	11 1/2
16	BA064	20 3/4	11 1/2
18	BA067	22 3/4	11 1/2
20	BA070	24 3/4	12 1/4

Fan Dia."	Model No.	Dimensions	
		A"	B"
<b>2-SPEED</b>			
12	BA482	17	11 1/2
14	BA483	18 3/4	11 1/2
16	BA484	20 3/4	11 1/2
18	BA485	22 3/4	11 1/2
20	BA486	24 3/4	12 1/4
24	BA487	28 3/4	12 1/4

## 18" FLOOR FAN

- 18" floor fan is ideal for different areas, from the store to the warehouse and for offices where air circulation is needed
- 3-prong plug with heavy-duty ground industrial wire
- Rear mounted controls
- Powerful, quiet 3-speed motor
- Rotates up for vertical airflow
- 120 V

Model No. BB116



## 20" BOX FAN

- Slim line
- 5 slim blades
- 3-speed whisper quiet operation
- Durable steel body
- No tools required for assembly

Model No. BA330



## AIR CONDITIONERS

Highly efficient whisper quiet models are designed for dependable long life use.

- Compact design fits most windows
- 3-setting thermostat
- 2-speed fan
- Washable rigid filter



Model No.	BTU	Remote Control	EER cooling	Dimensions			Wt. kg
				W"	x D"	x H"	
BB117	5,200	No	10	17.5	x 15.7	x 12.6	29
EA083	6,000	Yes	9.8	18	x 21.4	x 13.9	30
EA081	8,000	Yes	9.7	17.7	x 21.1	x 13.6	35
EA235	10,000	Yes	10	22	x 25.6	x 15.7	51

## AIR CONDITIONER AND MAJOR APPLIANCES EXTENSION CORDS

- Moulded-on bonded vinyl plugs and connectors won't break off or pull
- Cord resists cracking and breaking
- 3-conductor SPT-3
- 15 A, 1875 W
- 14/3 AWG



Model No.	Length'	Qty/Case
XC156	3	36
XC157	6	30

## OFFICE FANS

- Light duty all general purpose fans
- Best suited for office environments
- 3-speed oscillating except for EA068 which is 2 speed non-oscillating

Model No.	Description
EA068	6" Clip-on/Desk
BA175	12" Desk
EA070	16" Desk
EA071	16" Pedestal
EA073	16" Wall w/remote
BA778	18" Pedestal

EA073



EA068



EA071



## INDUSTRIAL ROLL-AIR MODEL CART MOUNTED 18" FAN

- Ideal for manufacturing, warehouses, workstations, etc.
- Cart features 5" diameter plastic wheel
- Cart height is fully adjustable from 33" to 50"
- 18" fan head is 3-speed
- Energy efficient – draws only 2.6 Amps

### SPECIFICATIONS:

- CFM: 5500 – high speed, 4600 – medium speed, 3500 – low speed
- Motor: 1/8 HP
- Weight: 24 lbs.

Model No. EA041



## 20" LIGHT INDUSTRIAL DUTY AIR CIRCULATOR

- Ideal for offices, retail, banks, hotels, etc.
- Energy efficient – draws only 2.1 Amps
- Rugged all metal construction – adjustable height up to 60"
- Pull chain switch – 3-speed control
- Double locking guard for safety
- 72" grounded power cord
- cUL US approved and also meets OSHA standards specifications
- CFM: 5950 – high speed, 3500 – low speed
- Motor: 1/6 HP drip proof motor
- Weight: 32 lbs.

Model No. EA009



1-year warranty!

