

BALANCERS & REELS

TOOLS BALANCERS

- Designed to enhance productivity, comfort and safety
- Protect tools from being damaged
- Aircraft (steel/nylon) cable and a standard 360° swivel hanger
- No force required to maintain load, light force to position load
- Installed easily in minutes
- Recommended that a secondary support chain/cable be attached to equipment suspended overhead

W Woodhead Canada Ltd.

| Model No. | Mfg. No. | Locking Model No. | Mfg. No. | Capacity lbs. | Cable Travel ft' | Duty |
|-----------|----------|-------------------|----------|---------------|------------------|-------|
| FA124 | GM-31 | - | - | 1-12 | 4.8 | Light |
| FA125 | RB2 | - | - | 1-2 | 5.2 | Light |
| FA126 | RB4 | - | - | 2-4 | 5.2 | Light |
| FA127 | RF6 | FA128 | RFL6 | 4-6 | 6.6 | Light |
| FA129 | RF8 | FA130 | RFL8 | 6-8 | 6.6 | Light |
| FA131 | BF9 | FA132 | BFL9 | 6-9 | 6.6 | Light |
| FA133 | BF13 | FA134 | BFL13 | 9-13 | 6.6 | Light |
| FA135 | BF18 | FA136 | BFL18 | 13-18 | 6.6 | Light |



FA124

FA125 - FA130



TOUGH IMPACT & CORROSION-RESISTANT UV STABILIZED PVC REELS

AIR OR WATER REELS - WORKING TEMPERATURES FROM -5° TO 60°C - SOLD WITH HOSE

Innovative features include:

- Full flow brass swivel
- Highest quality ground edge spring
- All position locking system
- Unique ratchet style tensioning system
- Innovative swivel mounting system
- Replaceable protective mouth guard
- Large side plates for easy access swivel maintenance
- Unique servicing safety locking pin system

| Model No. | Drive Type | Hose I.D." | Hose Length' | Max PSI | Hose Outlet" (M) NPT | Reel Inlet" (F) NPT | Reel Outlet" (F) NPT | Depth | Dimensions" Width | Height | Shipping Wt (lbs) |
|-----------|------------|------------|--------------|---------|----------------------|---------------------|----------------------|--------|-------------------|--------|-------------------|
| FH510 | Spring | 3/8 | 50 | 240 | 3/8 | 3/8 | - | 22 1/8 | 9 1/2 | 19 3/8 | 25.5 |
| FH511 | Spring | 3/8 | 65 | 240 | 3/8 | 3/8 | - | 22 1/8 | 9 1/2 | 19 3/8 | 25.5 |
| FH512 | Spring | 1/2 | 50 | 240 | 3/8 | 1/2 | - | 22 1/8 | 9 1/2 | 19 3/8 | 25.5 |
| FH513 | Spring | 1/2 | 60 | 240 | 3/8 | 1/2 | - | 22 1/8 | 9 1/2 | 19 3/8 | 25.5 |

REELCRAFT



FH510

HOSE REELS

- Durable, corrosion-resistant powder coat paint
- Heavy-duty, reinforced steel stampings for increased strength
- Permanently lubricated for long, trouble-free service
- Multi-position guide arms for versatile mounting options
- Kinkless, high quality hoses
- Spring rewind features long life spring with declutching arbour

REELCRAFT



FH494



TN315

HEAVY-DUTY INDUSTRIAL PVC REELS

| Model No. | Mfg. No. | Drive Type | Hose I.D." | Hose Length' | Max PSI | Outlet" (M) NPT | Inlet" (F) NPT | Outlet" (F) NPT | Depth | Dimensions" Width | Height | Wt. lbs. |
|-----------|------------|------------|------------|--------------|---------|-----------------|----------------|-----------------|--------|-------------------|--------|----------|
| TN315 | 4435-OLP | Spring | 1/4 | 35 | 300 | 1/4 | 3/8 | n/d | 12 5/8 | 5 3/8 | 12 7/8 | 20 |
| TN317 | 4625-OLP | Spring | 3/8 | 25 | 300 | 1/4 | 3/8 | n/d | 12 5/8 | 5 3/8 | 12 7/8 | 22 |
| TN316 | 5635-OLP | Spring | 3/8 | 35 | 300 | 1/4 | 3/8 | n/d | 13 1/2 | 6 | 14 1/2 | 25 |
| FH533 | 5650-OLP | Spring | 3/8 | 50 | 300 | 1/4 | 3/8 | n/d | 16 1/2 | 6 | 17 1/2 | 36 |
| TN318 | 7650-OLP | Spring | 3/8 | 50 | 300 | 1/4 | 1/2 | n/d | 19 | 7 | 20 1/4 | 47 |
| FH534 | 81100-OLP | Spring | 3/8 | 100 | 300 | 3/8 | 3/8 | n/d | 24 | 10 1/2 | 25 3/8 | 112 |
| TN319 | 7850-OLP | Spring | 1/2 | 50 | 300 | 1/4 | 1/2 | n/d | 19 | 7 | 20 1/4 | 51 |
| FH490 | 82100-OLP | Spring | 1/2 | 100 | 300 | 1/2 | 1/2 | n/d | 24 | 10 1/2 | 25 3/8 | 121 |
| FH491 | 83050-OLP | Spring | 3/4 | 50 | 250 | 3/4 | 3/4 | n/d | 24 | 10 1/2 | 25 3/8 | 108 |
| FH492 | D83075-OLP | Spring | 3/4 | 75 | 250 | 3/4 | 3/4 | n/d | 24 | 14 1/4 | 25 3/8 | 132 |
| FH493 | D84050-OLP | Spring | 1 | 50 | 250 | 3/4 | 1 | n/d | 24 | 15 1/4 | 25 3/8 | 130 |
| FH494 | E9350-OLP | Spring | 3/4 | 50 | 250 | 3/4 | 3/4 | n/d | 26 1/4 | 15 3/4 | 26 1/4 | 160 |
| FH495 | E9450-OLP | Spring | 1 | 50 | 250 | 3/4 | 1 | n/d | 26 1/4 | 15 3/4 | 26 1/4 | 177 |

STAINLESS STEEL FOR AIR, WATER OR OIL - CORROSION-RESISTANT REELS - SWIVELS INCLUDE VITON® "O" RINGS - SOLD WITHOUT HOSE

| Model No. | Mfg. No. | Drive Type | Hose I.D." | Hose Length' | Max PSI | Outlet" (M) NPT | Inlet" (F) NPT | Outlet" (F) NPT | Depth | Dimensions" Width | Height | Wt. lbs. |
|-----------|----------|------------|------------|--------------|---------|-----------------|----------------|-----------------|--------|-------------------|--------|----------|
| FH503 | 5600-OLS | Spring | 3/8 | 35 | 500 | n/d | 3/8 | 3/8 | 13 3/4 | 6 | 14 1/2 | 23 |
| FH504 | 7800-OLS | Spring | 1/2 | 50 | 500 | n/d | 1/2 | 1/2 | 19 | 7 | 20 1/4 | 44 |
| FH505 | 7800-OMS | Spring | 1/2 | 50 | 3000 | n/d | 1/2 | 1/2 | 19 | 7 | 20 1/4 | 47 |

FH503



MANUAL REWIND AIR HOSE REELS

- All weather design for indoor or outdoor use
- Rugged unlitised bolted construction
- Heavy gauge steel reel frame, spool, and drum
- Drag spring reduces self-unwinding
- Holds 3/8" ID hose (Sold separately)
- 3/8" brass NPT fittings
- 250 PSI/16.7 Bar maximum working pressure
- Corrosion resistant powder coated finish
- Heavy gauge welded mounting bracket (Hardware included)

| Model No. | Length' | Wt. lbs. |
|-----------|---------|----------|
| FH463 | 50 | 9.7 |
| FH464 | 100 | 13.2 |



FH463

LIND EQUIPMENT LTD.

B55