

# LIFT TABLES & SKID LIFTS

## HYDRAULIC LIFT TABLES

- Foot operated lifts are ideal for wide variety of shop functions (lifting dies, transporting heavy parts and positioning materials)
- Hand operated lever lowers the table level and controls the rate of descent
- All welded units
- Telescoping posts for stability and support
- Tops are 3/16" thick steel
- 4" x 2" roller bearing phenolic casters
- Capacity: 2500 lbs.



Model No.	Table Height		Table Size		Wt. lbs.
	Lowered"	Raised"	Width" x Depth"		
MG782	31	50	18 x 18		170
MG783	31	50	18 x 36		225
MG784	31	50	24 x 36		255
MG785	31	50	30 x 42		325



MG782



MG784

## STAINLESS STEEL HYDRAULIC SCISSOR LIFT TABLES

- Ideal for use in corrosive and wet environments
- Portable ergonomic stainless steel carts eliminate worker bending and lifting while providing maximum protection from corrosion
- Can also be used in conjunction with food grade hydraulic oil for food service applications
- All components assembled from high quality stainless steel except hydraulic cylinder and casters
- Foot pump includes a soft-lowering down valve
- Includes: Four polyurethane casters, two swivel with brakes, and two rigid for mobility



MK812



MK813



Model No.	Platform Width"	Size Length"	Capacity lbs.	Table Lowered"	Height" Raised"	Wt. lbs.
MK812	19.5	31.5	550	9.75	33.5	160
MK813	23.5	35.5	1100	13	38.5	240

## HYDRAULIC SKID LIFTS/TABLES

- Transport and position skids, wire baskets and containers to comfortable working heights
- Add optional slip-on table top create a mobile, variable height work table
- Lifting range is from 3 1/4" to 32 3/4"
- Heavy gauge steel construction
- 6" polyurethane swivel casters in the rear, 3" x 4" load wheels on legs
- Locking foot break
- Double roller chain lifts forks evenly and smoothly
- Lifting for 1000-lbs. capacity is accomplished with a hydraulic foot pedal
- 2200-lbs. capacity comes with an off-set steering wheel and control (pump) handle that elevates forks
- Approx 50 strokes to reach maximum height
- Release knob on handle lowers forks
- 62" truck length
- Not designed for lifting double-sided pallets



Model No.	Fork Width"	Fork Length"	Capacity lbs.	Wt. lbs.
MK792	20 1/2	42 1/2	1000	226
MA445	20 1/2	42 1/2	2000	323
MK793	27	42 1/2	1000	238
MA447	27	42 1/2	2000	334

## SCISSOR LIFT TABLE

This lift table is built of rugged construction, with heavy gauge steel and sturdy continuous welds throughout. Equipped with a steel work platform and high quality casters with bearings for greater maneuverability. Superior hydraulic system includes a chromed long-life cylinder. The surfaces are degreased and a quality baked enamel finish is applied. Table is able to lift a capacity of 660 lbs.

Table size: 20 1/2" x 39 3/4".  
Overall dimensions:  
48 1/2" x 20 1/2" x 37 3/4".  
**Minimum lifting height: 17"**  
**Maximum lifting height: 62 1/8"**  
Model No. MH210



## OPTIONAL TABLES

Model No.	Description	Wt. lbs.
MK794	Optional Slip-On Table for MK792	35
MK796	Optional Slip-On Table for MA445	35
MK795	Optional Slip-On Table for MA793	44
MK797	Optional Slip-On Table for MA447	44

## EZ LOADER PALLET LIFTERS

Automatically positions the pallet to the proper height for on or off-loading. Minimizes bending and lifting, reduces extra movement around the pallet. The EZ Loader is weight sensitive: it raises and lowers the pallet as the load weight changes, keeping the top of the load at a convenient working height. Rotating top minimizes walking or reaching during the loading process. Allows on or off loading to be done from the near side and at a convenient height. Use 75 PSI pressurized air to initially pressurize the Firestone Airstroke Actuator™; a bleed valve allows adjusting of height to exact requirements. Adjustable to handle loads from 850 to 4500 lbs. or 450 to 3000 lbs., depending on model. Heavy-duty, structural steel frame is 30" x 50 1/2" at base; turntable is 43" in diameter.

\* Inquire about stainless steel EZ Loader pallet lifters

Model No.	Capacity Range	PSI	Height Range"	Wt. lbs.
MA500	450 to 3000 lbs.	75	8 3/4 - 30	500
MA501	850 to 4500 lbs.	65	8 3/4 - 30	525

