

DRUM INSERTS & LIDS

ACCORDION INSERTS FOR 55-GALLON DRUMS

- Seamless insert constructed from FDA approved LDPE, average 15 mil thick
- Accordion pleat design adjusts to varying heights of reconditioned drums
- Formed lip grips chime of drum and stays in place during follower plate pumping



Model No.	Wall Thickness	Qty /Case
DA110	15 mil	20
DA911	18 mil	15
DA912*	15 mil	20

* Anti-static

INSERTS FOR 5-GALLON STEEL PAILS

- Constructed from FDA approved polyethylene
- Straight-sided inserts for steel pails are ideal for small batch mixing
- Choose from pliable LDPE or solvent-resistant HDPE
- Available in anti-static
- Available in polypropylene for hot-fill applications to 300°F
- Model DA945 used for hot-fill applications



Model No.	Wall Thickness	Material	Qty /Case
DA100	15 mil	LDPE	100
DC013	15 mil	HDPE	100
DA945	15 mil	Polypropylene	100

STRAIGHT-SIDED INSERTS FOR 16, 30 AND 55-GALLON OPEN HEAD STEEL DRUMS

- Constructed from FDA approved LDPE,
- Smooth wall inserts withstand mixing and pumping applications
- Available in anti-static
- Available in polypropylene for hot-fill applications to 440°F
- Model DC045 used for hot-fill applications



Model No.	Wall Thickness	Drum Gal.	Qty /Case
DC046	15 mil	16	15
DA868	15 mil	30	25
DA913	15 mil	55	20
DA914	18 mil	55	15
DA915	24 mil	55	15
DC045	15 mil	55	10

5-GALLON PLASTIC PAIL INSERTS

- Seamless 14" tall tapered insert provides custom fit for plastic pail
- Average 15-mil thick FDA approved LDPE or HDPE



Model No.	Material	Qty /Case
DB017	HDPE	100
DC048	LDPE	100

FUSIBLE LINK SELF-CLOSING DRUM COVER

- Converts open top 45-gallon steel drums into fire-safe receptacles for combustible trash
- Replaceable fusible link assembly inside the cover melts at 160°F, automatically slamming the cover shut if a fire occurs in the drum
- Steel construction; solvent resistant, red baked-on enamel finish
- Fits drums from 22 1/2" to 22 3/4" in diameter
- FM approved
- Wt.: 16 lbs.



Model No. DA097

ELASTICIZED DUST CAPS FOR 5, 30 & 55-GALLON CONTAINERS

- Clear 4 mil LDPE caps with elasticized band for easy installation
- Available in anti-static



Model No.	Drum Size	Model No.	Drum Size
DA106	5 gal.	DA930*	30 gal.
DA928*	5 gal.	DA107	45 gal.
DA929	30 gal.	DA931*	45 gal.

*Anti-static models

PROTECTIVE 55-GALLON DRUM LIDS

- Tough average 40-mil thick LDPE lids protect steel drum tops from corrosion and contamination
- Available for open head and tight head drums
- Available in clear to view labelling on drum top

Model No.	Description
DA116	Open Head Drum, Black Lid
DA117	Open Head Drum, Clear Lid
DA118	Tight Head Drum, Black Lid
DA119	Tight Head Drum, Clear Lid



HORIZONTAL VENTS

- FM approved vents are for use with drums in the horizontal pouring position
- Automatically relieves pressure at 5 PSI
- Flame arrestor protects contents
- Manual vacuum relief by lifting and rotating valve stem
- Maximum flow of 220 CFM at 20 PSI
- Fits 2" NPT bung in steel and plastic drums
- Use **brass vent** for petroleum based applications
- Use **stainless steel vent** for corrosives and general solvents



Model No.	Description	Wt. lbs.
DA604	Brass vent	1.0
DA608	Stainless steel vent	1.0

VERTICAL VENTS

- FM approved vents are for use with drums in the upright position
- Valve automatically opens to relieve internal pressure at 5 PSI
- Automatic vacuum relief permits 4 GPM flow through 3/4" faucet
- Fits 2" NPT bung opening



Model No.	Description	Application	Wt. lbs.
DA607	Brass vent	Petroleum-based	0.5
DA605	Non-metallic vent, cad-plated flame arrestor	Petroleum-based	0.5
DA606	Non-metallic vent, stainless steel flame arrestor	Chlorinated solvents	1.0