WATER COOLERS

INDUSTRIAL WATER COOLERS

 Heavy-duty blow moulded resin resists chips and dents in the toughest work area or job site

 Injection grade insulated liner material keeps your water or beverage cold

· Leak-resistant screw on lid

· Drip-resistant spigot

· Sturdy moulded-in handles on the 10 gallon

 Universal cup dispenser is available for 3 gallons and up, holds 200 cups



Model No.	Description	Wt. lbs.			
NI653	3 Gallons	5.4			
NI654	5 Gallons	7.5			
NI655	5 Gallons/w Dispenser	7.5			
NI656	10 Gallons	10.9			
NI657	Universal Cup Dispenser	4.9			

DRINKING WATER FILTER FOR OASIS® COOLERS

 Removes dirt, cloudiness, particles, unpleasant odours and taste

 Reduces chlorine by 97%, lead between 95.9% and 99% and cryptosporidium and giardia cysts by 99.99%

 Works with all the Oasis® water coolers listed on this page

Includes brackets, complete filter and colour coded waterline connections

 Fast and easy-to-change refill cartridges with automatic shut-off valve inside the filter

 Designed to last 1,500 gallons or approximately six months

Model No. OG445 Filter Model No. OG446 Refill cartridge



OASIS WATER COOLERS

Oasis® water coolers are manufactured with a heavy gauge steel frame which provides durable and quiet operation. They feature a 5-year limited warranty on the sealed refrigeration system and most component parts. All waterways are constructed of lead free materials and HFC 134A is used as a refrigerant. No CFCs are used. All units are standard Tan Sandstone finish. Drinking water temperature is 50°F/10°C.



WALL-MOUNTED COOLERS

These units come in standard or compact models. All units are shipped with complete instructions and wall mounting bracket. Units should be installed with the nozzle 36 inches from the floor.

Model No.	Mfg.		GPH	Dimensions					Wt.
	No.	Description	Capacity	W"	х	Н"	х	D"	lbs.
OJ952	PLF4CM	Compact	4	17	х	16	х	13 3/16	51
OA061	P8M	Standard	8	17	Х	14	Х	29 7/8	73
0Δ536	P14M	Standard	14	17	v	14	v	29 7/8	76



FREE-STANDING COOLERS

COMPACT FREE STANDING

Attractive economical line suitable for applications in offices, shops or factories where space saving is critical. Size 12" W x 43 3/4" H x 12" D.

Model Mfg.			GPH	Wt.	
No.	No.	Description	Capacity	lbs.	
OA063	P3CP	Compact	3	66	
OA064	P5CP	Compact	5	69	
OA548	P10CP	Compact	10	73	

AGAINST-A-WALL OR FREE-STANDING COOLERS

All plumbing connections are completely sealed within the cabinet, permitting flush-to-wall installation. Size: 17" W \times 43 3/4" H \times 14" D.

Model	Mfg.		GPH	Wt.	
No.	No.	Description	Capacity	lbs.	
OC709	P8FA	Standard	8	94	
OA545	PLF8FAH	Hot 'N' Cold*	8	98	
OA550	P14FA	Standard	14	96	
OC712	PLF14FAH	Hot 'N' Cold*	14	99	

^{*} Hot 'N' Cold models deliver 45 six ounce cups of hot water per hour in addition to cold water. Glass filler included.





OA063

HEAVY-DUTY & LARGE CAPACITY COOLERS

Constructed of 18 gauge steel cabinet with 16 gauge steel base. Handsome yet rugged design allows for installation in any environment.

Model Mfg.			GPH		D	Wt.			
No.	No.	Description	Capacity	W"	х	H"	х	D"	lbs.
OC713	P7P	Whisper Quiet	7	15	Х	43 3/4	Х	15	73
OA056	P13P	Standard	13.5	15	Х	43 3/4	Х	15	81
OC823	PLF20FA	Standard	19.5	17	Х	43 7/8	Х	11	91

B152