

# CORD REELS & WORK LIGHTS



## WORKLIGHTS

- Weatherproof
- Tempered glass lens
- Chrome-plated, solid steel guard
- Shock-resistant double insulated wiring
- 500 watt colour-corrected quartz halogen bulb included
- 16-gauge heavy-duty chemical and abrasion resistant cord
- Powder-coated steel construction
- Rubber leg tips protect floors and surfaces
- 1 year limited warranty



### 1' TO 3' TELESCOPIC

- 8' cord
- Collapsible steel base
- Lights up to 6,000 sq. ft.

Model No. XA150

### 4' TO 8' TELESCOPIC

- Double-reinforced sandbaggage steel base expands to 48"
- 15' cord
- Lights up to 7,000 sq. ft.

Model No. XA140

### 4' TO 8' TELESCOPIC TWIN

- Twin head independently adjustable 360°
- Two 10-A switches
- Double-reinforced sandbaggage steel base expands to 48"
- 15' cord
- Lights up to 14,000 sq. ft.

Model No. XA141

### REPLACEMENT BULB ON ALL 3 STYLES

Model No. XB149



## PORTABLE HALOGEN WORK LIGHT

- Quartz halogen fixture
- 500 watt bulb included
- Colour: Black and yellow
- CSA approved

Model No. XA992

### REPLACEMENT BULB

Model No. XB149



## WEATHERPROOF QUARTZ HALOGEN FIXTURES

- Double fixture with adjustable tripod
- 500 W bulbs included
- Extended height: 7'
- CSA approved
- Colour: Yellow

Model No. XA007

### REPLACEMENT BULB

Model No. XB149



## WORK REELS

### INCANDESCENT WORK LIGHT REEL

Incandescent work light is rated for a 75 W bulb. Includes switch and circuit breaker protected convenience outlet. Grounded metal guard with reflector protects the bulb.

### EXTENSION REEL

Triple outlet extension reel with reel circuit breaker.

### 13 W FLUORESCENT WORK LIGHT REEL

Includes switch, hanging hook, and full-length reflector. Rugged polycarbonate shield is easily removed for tool-free lamp replacement. Light output is 900 lumens.



Model No. Description

### INCANDESCENT WORK LIGHT REELS

XA640	20' 18/3 SVT cord, 7 A rating
XA155	30' 16/3 SJT cord, 10 A rating
XA921	50' 18/3 SVT cord, 7 A rating

### EXTENSION REELS

XA154	30' 16/3 SJT cord, 10 A rating
XB281	30' 14/3 SJT cord, 13 A rating

### FLUORESCENT WORK LIGHT REEL

XA289	40' 18/2 SJT cord
XA412	30' 16/3 SJT cord, 10 A outlet in light



## FLUORESCENT WORK LIGHTS

- Cool running
- Shatter resistant polycarbonate tube
- Includes enclosed starter switch, rubber end caps, a full-length reflector, and hanging hook
- Moisture and dust resistant
- Light output is 900 lumens
- Colour: Yellow
- 25'. 18/2 SJTOW cord

Model No. XA146

13 W, 10" length

Model No. XA149,

15 W, 22" length



## INCANDESCENT HAND LAMPS

- 100-W explosion proof light provides 1600 lumens of light output
- CSA and UL approved for Class Division I Group C and D hazardous locations
- 16/3 SOOW cord with a non-explosion proof plug (explosion proof plug is also available)

Model No. XA269 25' cord

Model No. XA103 50' cord

### REPLACEMENT BULB

Model No. XB123



## INCANDESCENT WORK LIGHTS

- Rated for a 100 W bulb
- Protected by heavy-gauge metal guard and reflector
- Includes circuit breaker protected convenience outlet, rated for a full 15 A capacity
- Colour: Yellow
- 14/3 SJTOW cord

Model No. XA175, 25'

Model No. XA918, 50'



B184

## RECHARGEABLE AC/DC WORK LIGHT

- 60 LEDs up to 100,000-hour bulb life
- Durable ABS plastic
- Up to 8 hours on a full charge
- Impact, oil and water resistant
- Includes: Charger, car charger and powerful magnet

Model No. XC233



## FLUORESCENT WORK LIGHTS

- Cool running fluorescent bulb
- Shatter resistant polycarbonate lamp shield
- Includes: full length reflector, switch and hook
- Models XB906, XB907 and XB967 also have a magnet mount and outlet



Model No. Description Length"

### COMPACT TWIN-TUBE

XB906	13 W, 25' Cord, 16/3 SJT	13
XB907	13 W, 50' Cord, 16/3 SJT	13
XB967	26 W, 25' Cord, 16/3 SJT, Dual Twin-Tube	15

XA251 Replacement Bulb

### LINEAR FLUORESCENT

XB968	15 W, 25' cord, 18/2 SJT	26
XA572	Replacement Bulb	

## LED WORK LIGHT

- 60 LED lights
- Heavy-duty 15' AC cord
- Heavy-duty 110 V adaptor
- 100,000 hours bulb life
- Water and oil resistant
- Hanging hook
- Unique On/Off switch

Model No. XC355

