


# WORK PLATFORMS & SCAFFOLDING

## HIGH WORK MAINTENANCE PLATFORMS

- Convert forklift truck into safe, efficient work platform
- Take care of overhead maintenance problems without setting up ladders or scaffolds
- Non-skid platform
- 72" safety mesh backscreen keeps operator and equipment away from lift mechanism
- Forks slip easily into pockets then attach safety chains
- Load capacity: 600 lbs
- No assembly required

### NOTE:

Kleton Maintenance Platforms meet or exceed ASME B56.1 safety standard when a safety harness and lanyard are worn.



MD948



MD444

| Model No. | Description                             | Wt. lbs. |
|-----------|---|----------|
| MD444     | High Work Platform - 36" x 36" platform | 230      |
| MH800     | High Work Platform - 48" x 48" platform | 300      |
| MD338     | Optional 6" caster kit                  | 10       |
| MD948*    | Light Bulb Caddy 15" W x 15" D x 43" H  | 25       |

### OPTIONAL TOOL TRAYS

|       |  |
|-------|--|
| MI787 | 36" L x 4" W x 3" D, Fits on model MD444 |
| MI788 | 48" L x 4" W x 3" D, Fits on MH800       |

\* Mounts on models MD444 and MH800.



## EMERGENCY STOP SWITCH

- Safety kill switch for person on work platform
- Will cut power to forklift in case of an emergency
- Consists of control box for platform, plug-in box (to be installed on forklift), and wire that extends 6' to 20'
- Switch is easy to install
- Recommended for maintenance platform model MD444 and MH800



| Model No. | Description           |
|-----------|-----------------------|
| MD328     | Emergency Stop Switch |

## RETRACTABLE WEB LANYARD

NORTH

- 8' (2.4 m) long with locking swivel snap hook
- Will "lock up" in approximately 9" (230 mm) thereby limiting overall exposure to a fall
- Provides maximum protection in places where lanyards might get in the way
- Equipped with 2" (50 mm) webbing, a tough vinyl cover and mounting karabiner
- CSA type: Fall arrest type 1

Model No. SN122 Mfg. No. FP0304



## DURABUILT HARNESSES

- Priced right to satisfy your needs, without sacrificing quality
- Lightweight, user friendly
- Polyester webbing for greater resistance to chemicals
- Large back D-ring
- Universal size fits most
- Available in other sizes
- Meets and exceeds all standards CSA, ANSI and OSHA

Model No. SAH533 MFG No. FPD6981DP

NORTH



## MOVABLE SCAFFOLDING

### A. ROLLING SCAFFOLD

- Adjustable every 4" with maximum platform height of 6'
- Allows workers to safely reach variety of heights
- Compact - can pass through standard doorways and down narrow aisles
- 5" swivel casters with brakes
- Overall dimensions: 6' W x 28" D x 6' H
- 700 lbs. static capacity
- Shipped knocked down



A.

### B. MAXI-FOLD SCAFFOLD

- Foldable scaffold has platform that adjusts on 4" increments
- One piece frame assembly, three 8 1/8" x 75" steel platforms and four 5" casters with brakes
- Overall dimensions: 75 1/2" W x 29" D x 78" H
- Vertical extensions available
- Frame is painted using a polyester powder coating
- 700 lbs. static capacity
- Shipped knocked down



B.

|    | Model No. | Description           | Wt. lbs. |
|----|-----------|-----------------------|----------|
| A. | MB035     | Rolling Scaffold      | 150      |
| B. | MB086     | Maxi-Fold             | 129      |
|    | MB087     | 3' Vertical Extension | 40       |
|    | MB088     | 6' Vertical Extension | 49       |

## FORTRUSS® STEEL ROLLING TOWER SCAFFOLD (SS SERIES)

The scaffolds include guard-rail system which are easily assembled or adjusted by just one person. Fortruss® may be stacked, utilizing up to 3 units to a maximum of 15'. Outriggers are required when stacking over 6'.

- Pistol grip for easy one-man height adjustment
- Caster stem snaps into frame securely with no chance of caster drop-out
- Expanded end frame tube ends with locking tab making it easy to lock stacked sections or casters into place
- Tightening 'L' knob for better connection between truss and end frame increases stability
- Dual-lock casters are 5" x 1 3/8"
- Rectangular steel tubing end frame with round rungs
- Exterior grade plywood platform: 5/8" thick x 29" W x 65 3/8" L or 89 3/8" L



| Model No. | Size L' x H' | End Frames     | Truss Assembly | No. Plywood Platform(s) | No. of Casters | Wt. lbs. |
|-----------|--------------|----------------|----------------|-------------------------|----------------|----------|
| MF424     | 6 x 3        | 2 x 3'         | 2 x 6'         | 1                       | -              | 112      |
| MF425     | 8 x 3        | 2 x 3'         | 2 x 8'         | 1                       | -              | 127      |
| MF426     | 6 x 6        | 2 x 6'         | 2 x 6'         | 1                       | 4              | 154      |
| MF427     | 8 x 6        | 2 x 6'         | 2 x 8'         | 1                       | 4              | 171      |
| MF428     | 6 x 12       | 4 x 6'         | 4 x 6'         | 2                       | 8              | 418      |
| MF429     | 8 x 12       | 4 x 8'         | 4 x 8'         | 2                       | 8              | 463      |
| MF430     | 6 x 15       | 4 x 6', 2 x 3' | 6 x 6'         | 3                       | 8              | 530      |
| MF431     | 8 x 15       | 4 x 6', 2 x 3' | 6 x 8'         | 3                       | 8              | 590      |

### SPECIFICATIONS:

End frames - full height unit 29" W x 68" H (w/o casters)

- half unit 29" W x 39" H (w/o casters)

Width (assembled) - 29 1/2" (w/o casters)

Platform height max. (w/casters) - 6' unit: 6' 3"

- 12' unit: 11' 8"

- 15' unit: 14' 10"

Load capacity - 6' L unit: 655 lbs. (50 lbs./sq. ft.)

- 8' L unit: 450 lbs. (25 lbs./sq. ft.)

Please Note: Do not stack higher than 3 units totalling 15'.

Each set of end frames requires one pair of trusses and platform (incl. w/shipment).

Outrigger kit and guard-rail/toeboard kit shipped with unit when platform is more than 10' above floor surface.



MF426



B75

# SHOWERS & FALL PROTECTION

## COMBINATION SHOWER/EYEWASH

Easy-to-install combination drench shower eyewash station should be located within 100 feet of hazardous areas, equipped with 1 1/4" IPS galvanized steel pipe, impact-resistant shower head and eyewash bowl. Stay open ball valves assure safe, hands-free operation. All units painted high visibility yellow and equipped with wall mount safety sign.

### DRENCH SHOWER TESTER

- Heavy-duty tester provides a convenient way to comply with ANSI specifications for weekly testing on all drench showers - without getting wet
- 84" long, watertight funnel with weighted bottom directs water to a drain or bucket
- 8' telescoping aluminum handle
- Testing record card included

**Bradley**

| Model No. | Description          | Wt. lbs. |
|-----------|----------------------|----------|
| SA415     | Combination Shower   | 60       |
| SC338     | Drench Shower Tester | 5        |

SA415



SC338



**Bradley**

## OVERHEAD SHOWERS

Drench showers provide fast drench of complete body in seconds. Hands-free ball valve activates immediately, 10" Impact resistant plastic shower head. Available for horizontal or vertical supply. SEI certified. Meets ANSI Z358.1 standards.

| Model No. | Description       | Wt. lbs. |
|-----------|-------------------|----------|
| SA414     | Horizontal Supply | 7        |
| SA416     | Vertical Supply   | 5        |

## EMERGENCY SHOWER STATION MAT NO. 465

Use under emergency showers or eyewash stations to draw attention to the emergency equipment and to keep accident victims from slipping.

- 7/8" thick with drainage ports throughout, keeps employees safely above the overflow area as the hazardous chemicals are washed off
- High-traction design on the mats surface also provides safe footing
- Following the ANSI Z535.1-1998 standard for colour-coding, the mat effectively calls attention to the safety shower (red) or eyewash areas (green)
- Highly visible tiles designate the location of first aid and safety equipment, and the yellow borders denote caution
- Borders are 6" wide and have a gradual slope for easy access

SA0082



**1-year warranty!**

SAN335



| Model No. | W" | Dim. x | L" | Colours |
|-----------|----|--------|----|---------|
| SAN335    | 30 | x      | 36 | Green   |
| SAN336    | 30 | x      | 48 | Green   |
| SA0082    | 30 | x      | 36 | Red     |
| SA0083    | 30 | x      | 48 | Red     |

## TITAN® CONTRACTOR'S HARNESSES

Titan™ full-body harnesses are made from lightweight durable polyester webbing for all day comfort and dependability.

- Fully adjustable design
- Sliding back D-ring
- Sub-pelvic strap
- Universal fit (other sizes available upon request)
- Colour: Orange
- Meets all applicable OSHA, ANSI and CSA requirements

**MILLER**  
by SPERIAN



| Model No. | Mfg. No.  | Side D-Rings | Shoulder Strap Buckles | Leg Strap Buckles | Chest Strap Buckle | CSA Group |
|-----------|-----------|--------------|------------------------|-------------------|--------------------|-----------|
| SN064     | T4000/UAK | No           | Mating                 | Mating            | Mating             | A         |
| SN065     | T4007/UAK | Yes          | Mating                 | Mating            | Mating             | A, P      |
| SN066     | T4500/UAK | No           | Mating                 | Tongue            | Mating             | A         |
| SN067     | T4507/UAK | Yes          | Mating                 | Tongue            | Mating             | A, P      |

## TITAN® SHOCK-ABSORBING LANYARDS

Titan™ lanyards are made of lightweight, durable polyester webbing, 6' (1.8 m) length and locking snap hook for the harness.

**Tubular built-in core style** features a built-in woven inner core which smoothly expands to reduce fall arrest forces, while the outer jacket serves as a back-up web lanyard.

Standard length is 6'; also available in lengths from 4' to 10'. Locking snap hook - 3/4" gate opening.

Model No. SN069

**MILLER**  
by SPERIAN

SN069



## MILLER® MANYARD® SHOCK-ABSORBING LANYARDS

With 20 years of design refinement, the Miller® Manyard® shock-absorbing lanyards are unsurpassed in the market.

- Special woven shock-absorbing inner core reduces fall arrest forces
- Heavy-duty tubular outer jacket serves as a back-up web lanyard
- Unique warning flag provides visual proof that a lanyard has been involved in a fall and should be removed from service
- Harness connection: locking snap hook



SC980



SC984

**MILLER**  
by SPERIAN

| Model No. | Mfg. No.     | Number of leg | Anchorage Connection | Length' |
|-----------|--------------|---------------|----------------------|---------|
| SC980     | 216WLS/4FTYL | One           | Locking Snap Hook    | 4       |
| SC981     | 216WLS/5FTYL | One           | Locking Snap Hook    | 5       |
| SC982     | 216WLS/6FTYL | One           | Locking Snap Hook    | 6       |
| SC983     | 216WLS/8FTYL | One           | Locking Snap Hook    | 8       |
| SC984     | 219WRS/4FTYL | One           | Locking Rebar Hook   | 4       |
| SC985     | 219WRS/5FTYL | One           | Locking Rebar Hook   | 5       |
| SC986     | 219WRS/6FTYL | One           | Locking Rebar Hook   | 6       |
| SC987     | 219WRS/8FTYL | One           | Locking Rebar Hook   | 8       |
| SAH529    | 231WRS/6FTYL | Two           | Locking Rebar Hook   | 6       |

## MILLER® POSITIONING & RESTRAINT LANYARDS

Nylon rope lanyards are recommended for "work positioning" and "restraint" only. Harness connection: Locking snap hook.

**MILLER**  
by SPERIAN



SA012

| Model No. | Mfg. No.       | Anchorage Connection | Length' |
|-----------|----------------|----------------------|---------|
| SA012     | 201RLS-2/4FTWH | Locking Snap Hook    | 4       |
| SA013     | 201RLS-2/6FTWH | Locking Snap Hook    | 6       |
| SA014     | 201RLS-2/8FTWH | Locking Snap Hook    | 8       |
| SD512     | 202RRS-2/4FTWH | Locking Rebar Hook   | 4       |
| SD513     | 202RRS-2/6FTWH | Locking Rebar Hook   | 6       |
| SD514     | 202RRS-2/8FTWH | Locking Rebar Hook   | 8       |

# FALL ARREST EQUIPMENT

## MINILITE™ FALL LIMITER

Quick-activating braking system that limits a free fall to inches. In contrast to shock-absorbing lanyards, a fall limiter eliminates the need for extended fall distance clearance. This minimizes the risk of injuries and makes rescue easy.

- Offers up to 11 feet of working capacity
- Lightweight, compact design – only 2.5 lbs.
- Corrosion-resistant interior, frame and components
- Visual load indicator
- High-impact protective outer cover
- Prominent reflective labeling
- Available with a variety of integral anchorage connectors
- Meets OSHA, ANSI, CSA Z259.2.2 type 1 and CE requirements



**MILLER**  
by SPERIAN

| Model No. | Description  |
|-----------|--|
| SG987     | With Steel Twist Lock Carabiner and Stainless Steel Swivel Shackle |
| SG988     | Without Anchorage Connector  |
| SG989     | With Steel Twist-Lock Carabiner                                    |

## RETRACTABLE WEB LANYARDS

- 8' (2.4 m) long w/locking swivel snap hook
- Retractable web lanyards are the lightest SRL's available
- Engineered to provide maximum protection in places where lanyards might get in the way
- Equipped with 2" (50 mm) webbing, a tough vinyl cover and mounting karabiner
- CSA type: Fall Arrest type 1

**NORTH**



### APPLICATIONS:

- General fall protection
- Stock pickers in warehouses
- Aerial lift applications (i.e. scissor-lifts)
- Also available in other configurations to suit a variety of applications upon request

Model No. **SN122**  
Mfg. No. FP0304

## WORKMAN™ HARNESSES

- Economical
- Abrasion-resistant, strong, durable webbing
- Yellow polyester webbing for high visibility
- Web retainer collars to keep excess webbing neat
- Easy to don and adjust
- *Qwik-Fit™* chest strap
- CSA certified
- Size: Standard
- Other sizes available upon request
- Meets OSHA regulations, and ANSI A10.32 and Z359.1

**SAP167**



**MSA**

| Model No.                | Mfg. No. | D-Rings |     |
|--------------------------|----------|---------|-----|
|                          |          | Back    | Hip |
| TONGUE BUCKLE LEG STRAPS |          |         |     |
| SAP167                   | 10072487 | Yes     | No  |
| SAP168                   | 10072491 | Yes     | Yes |
| QWIK-FIT™ LEG STRAPS     |          |         |     |
| SAP203                   | 10072479 | Yes     | No  |
| SAP166                   | 10072483 | Yes     | No  |

## DURABILT SERIES FROM NORTH

### FEATURES:

- Priced right to satisfy your needs
- User friendly
- Polyester webbing for greater resistance to chemicals
- Large Back D-ring
- Universal style with our one size fits most

### SAFETY & QUALITY

- Meets or exceeds all standards CSA, ANSI and OSHA
- North doesn't just make it, they make sure it works: North tests all products to all applicable standards to ensure your safety
- ISO 9001 manufacturing facility

### COST EFFECTIVENESS

- Basic universal harness for everyday use
- Requires less sizes to carry
- No bells and whistles
- Lightweight
- Everything you will need in one kit (bag included)
- No sacrificing of quality for a better price



**DURABILT**  
by NORTH

## HARNESSES

| Model No. | Mfg. No.    | Description                         |
|-----------|-------------|-------------------------------------|
| SAH533    | FPD698/1DP  | Full body harness                   |
| SAH534    | FPD698/1DGP | Full body harness w/grommetted legs |

## LANYARDS

Polyester decelerator energy absorbing lanyard with double locking snap hook harness connectors.

| Model No. | Mfg. No.   | Anchors Connectors        | Length' |
|-----------|------------|---------------------------|---------|
| SAH537    | FPD29811/4 | Double locking snap hook  | 4       |
| SAH750    | FPD29811/6 | Double locking snap hook  | 6       |
| SAH538    | FPD29819/4 | Double locking rebar hook | 4       |
| SAH761    | FPD29819/6 | Double locking rebar hook | 6       |

## WORKMAN™ ENERGY-ABSORBING LANYARDS

- Lightweight with a low-profile body
- Shock absorber includes a clear, durable protective cover over the labels to increase service life and allow for easy inspection
- Tear-tape design to keep fall arrest forces below 900 lbs.
- Choice of single-leg or twin-leg configuration
- Choice of adjustable or tie-back configuration
- Meets OSHA regulations, and ANSI A10.32 and Z359.1
- CSA certified

**MSA**



| Model No. | Mfg. No. | Description                               | Length' |
|-----------|----------|---|---------|
| SAP195    | 10072472 | Single-leg, tie-back w/LC locking snaps   | 6       |
| SAP196    | 10072474 | Single-leg, adjustable w/LC locking snaps | 6       |
| SAP197    | 10072475 | Twin-leg, adjustable w/LC locking snaps   | 6       |