


WORK PLATFORMS & SCAFFOLDING

HIGH WORK MAINTENANCE PLATFORMS

- Convert forklift truck into safe, efficient work platform
- Take care of overhead maintenance problems without setting up ladders or scaffolds
- Non-skid platform
- 72" safety mesh backscreen keeps operator and equipment away from lift mechanism
- Forks slip easily into pockets then attach safety chains
- Load capacity: 600 lbs
- No assembly required

NOTE:

Kleton Maintenance Platforms meet or exceed ASME B56.1 safety standard when a safety harness and lanyard are worn.



Model No.	Description	Wt. lbs.
MD444	High Work Platform - 36" x 36" platform	230
MH800	High Work Platform - 48" x 48" platform	300
MD338	Optional 6" caster kit	10
MD948*	Light Bulb Caster 15" W x 15" D x 43" H	25

OPTIONAL TOOL TRAYS

MI787	36" L x 4" W x 3" D, Fits on model MD444
MI788	48" L x 4" W x 3" D, Fits on MH800

* Mounts on models MD444 and MH800.

MOVABLE SCAFFOLDING

A. ROLLING SCAFFOLD

- Adjustable every 4" with maximum platform height of 6'
- Allows workers to safely reach variety of heights
- Compact - can pass through standard doorways and down narrow aisles
- 5" swivel casters with brakes
- Overall dimensions: 6' W x 28" D x 6' H
- 700 lbs. static capacity
- Shipped knocked down



B. MAXI-FOLD SCAFFOLD

- Foldable scaffold has platform that adjusts on 4" increments
- One piece frame assembly, three 8 1/8" x 75" steel platforms and four 5" casters with brakes
- Overall dimensions: 75 1/2" W x 29" D x 78" H
- Vertical extensions available
- Frame is painted using a polyester powder coating
- 700 lbs. static capacity
- Shipped knocked down



	Model No.	Description	Wt. lbs.
A.	MB035	Rolling Scaffold	150
B.	MB086	Maxi-Fold	129
	MB087	3' Vertical Extension	40
	MB088	6' Vertical Extension	49

FORTRUSS® STEEL ROLLING TOWER SCAFFOLD (SS SERIES)

The scaffolds include guard-rail system which are easily assembled or adjusted by just one person. Fortruss® may be stacked, utilizing up to 3 units to a maximum of 15'. Outriggers are required when stacking over 6'.

- Pistol grip for easy one-man height adjustment
- Caster stem snaps into frame securely with no chance of caster drop-out
- Expanded end frame tube ends with locking tab making it easy to lock stacked sections or casters into place
- Tightening 'L' knob for better connection between truss and end frame increases stability
- Dual-lock casters are 5" x 1 3/8"
- Rectangular steel tubing end frame with round rungs
- Exterior grade plywood platform: 5/8" thick x 29" W x 65 3/8" L or 89 3/8" L



Model No.	Size L' x H'	End Frames	Truss Assembly	No. Plywood Platform(s)	No. of Casters	Wt. lbs.
MF424	6 x 3	2 x 3'	2 x 6'	1	-	112
MF425	8 x 3	2 x 3'	2 x 8'	1	-	127
MF426	6 x 6	2 x 6'	2 x 6'	1	4	154
MF427	8 x 6	2 x 6'	2 x 8'	1	4	171
MF428	6 x 12	4 x 6'	4 x 6'	2	8	418
MF429	8 x 12	4 x 8'	4 x 8'	2	8	463
MF430	6 x 15	4 x 6', 2 x 3'	6 x 6'	3	8	530
MF431	8 x 15	4 x 6', 2 x 3'	6 x 8'	3	8	590

SPECIFICATIONS:

End frames - full height unit 29" W x 68" H (w/o casters)

- half unit 29" W x 39" H (w/o casters)

Width (assembled) - 29 1/2" (w/o casters)

Platform height max. (w/casters) - 6' unit: 6' 3"

- 12' unit: 11' 8"

- 15' unit: 14' 10"

Load capacity - 6' L unit: 655 lbs. (50 lbs./sq. ft.)

- 8' L unit: 450 lbs. (25 lbs./sq. ft.)

Please Note: Do not stack higher than 3 units totalling 15'.

Each set of end frames requires one pair of trusses and platform (incl. w/shipment).

Outrigger kit and guard-rail/toeboard kit shipped with unit when platform is more than 10' above floor surface.



EMERGENCY STOP SWITCH

- Safety kill switch for person on work platform
- Will cut power to forklift in case of an emergency
- Consists of control box for platform, plug-in box (to be installed on forklift), and wire that extends 6' to 20'
- Switch is easy to install
- Recommended for maintenance platform model MD444 and MH800



Model No.	Description
MD328	Emergency Stop Switch

RETRACTABLE WEB LANYARD

NORTH

- 8' (2.4 m) long with locking swivel snap hook
- Will "lock up" in approximately 9" (230 mm) thereby limiting overall exposure to a fall
- Provides maximum protection in places where lanyards might get in the way
- Equipped with 2" (50 mm) webbing, a tough vinyl cover and mounting karabiner
- CSA type: Fall arrest type 1

Model No. SN122 Mfg. No. FP0304



DURABUILT HARNESES

- Priced right to satisfy your needs, without sacrificing quality
- Lightweight, user friendly
- Polyester webbing for greater resistance to chemicals
- Large back D-ring
- Universal size fits most
- Available in other sizes
- Meets and exceeds all standards CSA, ANSI and OSHA

Model No. SAH533 MFG No. FPD6981DP



NORTH

FALL ARREST EQUIPMENT

MINILITE™ FALL LIMITER

Quick-activating braking system that limits a free fall to inches. In contrast to shock-absorbing lanyards, a fall limiter eliminates the need for extended fall distance clearance. This minimizes the risk of injuries and makes rescue easy.

- Offers up to 11 feet of working capacity
- Lightweight, compact design – only 2.5 lbs.
- Corrosion-resistant interior, frame and components
- Visual load indicator
- High-impact protective outer cover
- Prominent reflective labeling
- Available with a variety of integral anchorage connectors
- Meets OSHA, ANSI, CSA Z259.2.2 type 1 and CE requirements



MILLER
by SPERIAN

Model No.	Description
SG987	With Steel Twist Lock Carabiner and Stainless Steel Swivel Shackle
SG988	Without Anchorage Connector
SG989	With Steel Twist-Lock Carabiner

RETRACTABLE WEB LANYARDS

- 8' (2.4 m) long w/locking swivel snap hook
- Retractable web lanyards are the lightest SRL's available
- Engineered to provide maximum protection in places where lanyards might get in the way
- Equipped with 2" (50 mm) webbing, a tough vinyl cover and mounting karabiner
- CSA type: Fall Arrest type 1

NORTH



APPLICATIONS:

- General fall protection
- Stock pickers in warehouses
- Aerial lift applications (i.e. scissor-lifts)
- Also available in other configurations to suit a variety of applications upon request

Model No. **SN122**
Mfg. No. FP0304

WORKMAN™ HARNESSES

- Economical
- Abrasion-resistant, strong, durable webbing
- Yellow polyester webbing for high visibility
- Web retainer collars to keep excess webbing neat
- Easy to don and adjust
- Qwik-Fit™ chest strap
- CSA certified
- Size: Standard
- Other sizes available upon request
- Meets OSHA regulations, and ANSI A10.32 and Z359.1



SAP167

MSA

Model No.	Mfg. No.	D-Rings	
		Back	Hip
TONGUE BUCKLE LEG STRAPS			
SAP167	10072487	Yes	No
SAP168	10072491	Yes	Yes
QWIK-FIT™ LEG STRAPS			
SAP203	10072479	Yes	No
SAP166	10072483	Yes	No

DURABILT SERIES FROM NORTH

FEATURES:

- Priced right to satisfy your needs
- User friendly
- Polyester webbing for greater resistance to chemicals
- Large Back D-ring
- Universal style with our one size fits most

SAFETY & QUALITY

- Meets or exceeds all standards CSA, ANSI and OSHA
- North doesn't just make it, they make sure it works: North tests all products to all applicable standards to ensure your safety
- ISO 9001 manufacturing facility

COST EFFECTIVENESS

- Basic universal harness for everyday use
- Requires less sizes to carry
- No bells and whistles
- Lightweight
- Everything you will need in one kit (bag included)
- No sacrificing of quality for a better price



DURABILT
by NORTH

HARNESSES

Model No.	Mfg. No.	Description
SAH533	FPD698/1DP	Full body harness
SAH534	FPD698/1DGP	Full body harness w/grommetted legs

LANYARDS

Polyester decelerator energy absorbing lanyard with double locking snap hook harness connectors.

Model No.	Mfg. No.	Anchors Connectors	Length'
SAH537	FPD29811/4	Double locking snap hook	4
SAH750	FPD29811/6	Double locking snap hook	6
SAH538	FPD29819/4	Double locking rebar hook	4
SAH761	FPD29819/6	Double locking rebar hook	6

WORKMAN™ ENERGY-ABSORBING LANYARDS

- Lightweight with a low-profile body
- Shock absorber includes a clear, durable protective cover over the labels to increase service life and allow for easy inspection
- Tear-tape design to keep fall arrest forces below 900 lbs.
- Choice of single-leg or twin-leg configuration
- Choice of adjustable or tie-back configuration
- Meets OSHA regulations, and ANSI A10.32 and Z359.1
- CSA certified

MSA



Model No.	Mfg. No.	Description	Length'
SAP195	10072472	Single-leg, tie-back w/LC locking snaps	6
SAP196	10072474	Single-leg, adjustable w/LC locking snaps	6
SAP197	10072475	Twin-leg, adjustable w/LC locking snaps	6