

# CLOTH & DUCT TAPES

Whatever your industry – HVAC, automotive, agriculture, aviation, construction, entertainment, even nuclear – you'll find the best tape for your next job right here. Our comprehensive line of duct and cloth tapes is engineered to exacting specs. We've virtually eliminated de-lamination and film variability. No other line of cloth and duct tapes performs better than Shurtape. We make your job, and your life, easier.

Suitable for a wide variety of applications, Shurtape co-extruded utility tape is a terrific general purpose tape for everything from packaging, holding and sealing to seaming, bundling and repairing. We have grades that meet UL 723, a requirement for specialized jobs.

## CO-EXTRUDED DUCT

### PC 590

**Co-extruded  
Waterproof Backing  
Natural Rubber Adhesive**



For general use in packaging, bundling, sealing, seaming, repairing, holding and waterproofing. Good adhesion characteristics.

<b>Tensile</b> (lbs/in width)	20
<b>Adhesion to Stainless Steel</b> (oz/in width)	45
<b>Thickness</b> (mils)	7.0
<b>Elongation</b> (%)	15
<b>Maximum Service Temperature</b> (°F)	200
<b>Applicable Specifications</b>	—

### PC 595

**Co-extruded  
Waterproof Backing  
Natural Rubber Adhesive**



Excellent for non-critical, general purpose packaging, bundling, sealing, seaming, repairing and holding. Meets requirements of UL 723.

<b>Tensile</b> (lbs/in width)	20
<b>Adhesion to Stainless Steel</b> (oz/in width)	45
<b>Thickness</b> (mils)	8.0
<b>Elongation</b> (%)	15
<b>Maximum Service Temperature</b> (°F)	200
<b>Applicable Specifications</b>	26, 53

### PC 600

**Polycoated  
High Tack Adhesive  
Natural Rubber  
Adhesive  
Co-extruded**



General purpose use in industrial, plumbing, carpet, color coding, splicing, and other home and general repairs.

<b>Tensile</b> (lbs/in width)	22
<b>Adhesion to Stainless Steel</b> (oz/in width)	50
<b>Thickness</b> (mils)	9.0
<b>Elongation</b> (%)	10
<b>Maximum Service Temperature</b> (°F)	200
<b>Applicable Specifications</b>	—

### PC 618

**Light Industrial Grade  
Poly Cotton Cloth Duct Tape  
Natural Rubber  
Adhesive  
Co-extruded**



To seal cartons, bind books, repair seats, bundle wires, color code, splice, repair, seal hatch covers and cargo doors in the shipping industry. Use as a condensation barrier in appliance assemblies. Meets requirements of UL 723.

<b>Tensile</b> (lbs/in width)	27
<b>Adhesion to Stainless Steel</b> (oz/in width)	50
<b>Thickness</b> (mils)	10.0
<b>Elongation</b> (%)	15
<b>Maximum Service Temperature</b> (°F)	200
<b>Applicable Specifications</b>	34, 53

## SHURTAPE

Distributor: Dabco Industrial Supplies  
(800) 521-0049 - [www.dabco.ca](http://www.dabco.ca)

## NEW PRODUCTS

For tasks like asbestos abatement, mold remediation, and in-field packing, you need a tough tape.

Our rigorous-duty tapes stick for weeks, without fail, and leave no residue. When isolating rooms, or sealing walls, windows and doors, Shurtape helps deliver a solid barrier against particulate debris.

### PC 610

**Industrial Abatement Tape**  
Works in Cold Weather  
Aggressive Wet-Stick  
Superior Shear-to-Poly



10 mil Industrial grade cloth duct tape for sealing walls, doors and windows during mold/asbestos abatement and in rugged environments. Instant quick stick to poly-sheeting, metal and unpainted wood at temperatures as low as 25° F. Easy to use because it's easy to tear and it won't twist or curl off the roll.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	55
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### PC 629

**Contractor Grade**  
Excellent Cold  
Weather Performance  
New High-Tack Adhesive



11 mil Contractor grade cloth duct tape works at temperatures as cold as 25° F. Seals doors, walls and windows for mold and asbestos abatement. High-tack adhesive with superior shear performance grabs quickly and seals dependably. Does not twist or curl off the roll.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	65
Thickness (mils)	11.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

## COLORED DUCT

### PC 600

**Polycoated**  
**High Tack Adhesive**  
**Natural Rubber**  
**Adhesive**



General purpose use in industrial, plumbing, carpet, color coding, splicing, and other home and general repairs.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	9.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### PC 618

**Light Industrial**  
**Grade**  
**Poly Cotton**  
**Cloth Duct Tape**  
**Natural Rubber**  
**Adhesive**



To seal cartons, bind books, repair seats, bundle wires, color code, splice, repair, seal hatch covers and cargo doors in the shipping industry. Use as a condensation barrier in appliance assemblies. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	34, 53

### PC 619

**Specialty Grade**  
**Natural Rubber**  
**Adhesive**  
**Fluorescent Colors**



Waterproof backing, good conformability and range of fluorescent colors make this a natural fit for motorsports, motion picture and floral industries.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

1 ANSI No. 45.2.2	12 CID A-A 1492B	23 FAR 25.853	34 FSI 15/SDI 25	45 PPP-T-66E, Type I, Class 2*
2 ASME NQA-1	13 CID A-A-1586A	24 FSI 0/SDI 0	35 FSI 15/SDI 30	46 Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6
3 ASTM D 1974	14 CID A-A-1671B	25 FSI 0/SDI 5	36 FSI 25/SDI 50	47 Rule 41*
4 ASTM D 5330, Type II	15 CID A-A-1684C	26 FSI 5/SDI 5	37 L-T-80B	48 SAE-AMS-T-23397
5 ASTM D 5749, Type I, Class 2	16 CID A-A-1689B, Type I, Class 2	27 FSI 5/SDI 10	38 MIL-T-23397B AMDT 2 Type II*	49 Seal Classes A, B, C
6 ASTM D 5749, Type II, Grade B	17 CID A-A-1689B, Type II	28 FSI 5/SDI 15	39 NRC Guide 1.38	50 T-428
7 ASTM D 6123/D 6123M-97	18 CID A-A-180B, Type II, Grade A	29 FSI 10/SDI 10	40 PM-85 Tested	51 UL 181A-P/B-FX
8 ASTM D 5486M-99, Type III	19 CID A-A-180B, Type II, Grade B	30 FSI 10/SDI 35	41 PNS 8030-899-030	52 UL 1818-FX
9 ASTM D 5486M-99, Type IV	20 CID A-A-55809	31 FSI 15/SDI 40	42 PPP-T-0097E, Type II, Class A*	53 UL 723
10 ASTM D 5486M-99, Type V	21 CID A-A-883B, Type I	32 FSI 11/SDI 6	43 PPP-T-42C, Type I*	54 UL Listed
11 CID A-A-113D, Type I Class A	22 CID A-A-883B, Type II	33 FSI 15/SDI 20	44 PPP-T-60E, Type IV, Class I*	



## PROFESSIONAL GRADE DUCT

### PC 609

**Polycoated  
Aggressive Wet-stick  
Adhesive  
HVAC**



All-purpose cloth duct tape for HVAC sealing metal and flex duct work, patching and mending thermal insulation. Meets requirements of UL 723.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.5
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	24, 53

### SF 682

**Metalized Backing  
Natural Rubber Adhesive  
HVAC**



Used for air-tight and moisture-free sealing, seaming and joining aluminum-backed flex ducts and sealing metal ducts. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	11.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	24, 53

### PC 620

**Industrial Grade  
Cloth Duct Tape  
Natural Rubber Adhesive**



For use in HVAC, industrial, commercial, utilities, trucking and automotive applications. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	11.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	26, 53

### PC 621

**Contractor Grade  
Cloth Duct Tape  
Natural Rubber Adhesive**



Demanding HVAC applications to hold, seal, and seam sheet metal and flex duct, exhaust vents, and pre-formed insulation. Industrial splicing, holding, protecting and packaging. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	55
Thickness (mils)	11.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	26, 53

### PC 721

**Contractor Grade  
Co-extruded  
Natural Rubber  
Adhesive**



Perfect for HVAC applications, PC 721 has excellent unwind and easy tearability. Use when sealing and holding sheet metal duct work. This duct tape meets requirements of UL 723.

Tensile (lbs/in width)	32
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	11.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	26, 53

When your job depends on the right tape at the right time ask for Shurtape professional grade duct tape. The right tape can mean the difference between a job well done and a job done over. Our full line of tapes for "pros" meets your every need. Anywhere, anytime, Shurtape is ready to work.

### SHURTAPE

Distributor: **Dabco Industrial Supplies**  
(800) 521-0049 - [www.dabco.ca](http://www.dabco.ca)

# PERFORMANCE GRADE DUCT

## PC 622

**Premium Grade Cloth Duct Tape**  
**Stucco Application**  
**Natural Rubber Adhesive**



12.5 mil premium grade cloth duct tape used for protection of window and door frames during stucco application; high performance motorsports applications, and heavy duty bundling, holding, and splicing. Meets requirements of UL 723.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	55
Thickness (mils)	12.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	29, 53

## PC 625

**Military Grade Lusterless Natural Rubber Adhesive**  
**ASTM 5486 Tested**



Used for packaging, sealing, bundling and stage preparation. High performance, polyethylene coated, waterproof packaging tape that meets government specifications. ASTM 5486 tested.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	12.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	9, 44

## PC 657

**Premium Grade Co-extruded Quality Natural Rubber Adhesive**



Used in high performance motor sports applications, pre-manufactured housing and RV assembly, critical industrial applications, and for protection during metal peening operations. Meets requirements of UL 723.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	31, 53

## PC 658

**Super Bottom Board Tape**  
**Co-extruded Cloth Duct Tape**  
**Natural Rubber Adhesive**



Used for seaming and sealing bottom board materials in pre-manufactured homes and RVs during assembly, set-up, and maintenance. Also used for protection of surfaces in metal peening operations. Meets requirements of UL 723.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	85
Thickness (mils)	17.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	33, 53

## P-670

**Book Binding, HVAC Co-extruded Solventless Rubber Based Adhesive**  
**Rocketdyne RB0195-002 Listed**



Used for sealing and seaming applications in the HVAC industry. Other applications include protection, splicing, bundling and holding. Conformable, waterproof and Rocketdyne RB0195-002 tested.

Tensile (lbs/in width)	38
Adhesion to Stainless Steel (oz/in width)	95
Thickness (mils)	11.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	—

## P-69

**The Original Duct Tape Co-extruded Solventless Rubber-based Adhesive**  
**ASTM D5486M CID A-A-1586A Tested**



Used for waterproof sealing of containers and ductwork. Other applications include protection, splicing, bundling and holding in the aerospace industry. Highly conformable and waterproof.

Tensile (lbs/in width)	43
Adhesion to Stainless Steel (oz/in width)	134
Thickness (mils)	12.0
Elongation (%)	3
Maximum Service Temperature (°F)	—
Applicable Specifications	9, 13

1. ANSI No. 45.2.2

2. ASME NQA-1

3. ASTM D 1974

4. ASTM D 5330, Type II

5. ASTM D 5749, Type I, Class 2

6. ASTM D 5749, Type II, Grade B

7. ASTM D 6123/D 6123M-97

8. ASTM D 5486M-99, Type III

9. ASTM D 5486M-99, Type IV

10. ASTM D 5486M-99, Type V

11. CID A-A-113D, Type I Class A

12. CID A-A-1492B

13. CID A-A-1586A

14. CID A-A-1671B

15. CID A-A-1684C

16. CID A-A-1689B, Type I, Class 2

17. CID A-A-1689B, Type II

18. CID A-A-180B, Type II, Grade A

19. CID A-A-180B, Type II, Grade B

20. CID A-A-55809

21. CID A-A-883B, Type I

22. CID A-A-883B, Type II

23. FAR 25.853

24. FSI 0/SDI 0

25. FSI 0/SDI 5

26. FSI 5/SDI 5

27. FSI 5/SDI 10

28. FSI 5/SDI 15

29. FSI 10/SDI 10

30. FSI 10/SDI 35

31. FSI 15/SDI 40

32. FSI 11/SDI 6

33. FSI 15/SDI 20

34. FSI 15/SDI 25

35. FSI 15/SDI 30

36. FSI 25/SDI 50

37. L-T-80B

38. MIL-T-23397B AMDT 2 Type II\*

39. NRC Guide 1.38

40. PM-85 Tested

41. PNS 8030-899-030

42. PPP-T-0097E, Type II, Class A\*

43. PPP-T-42C, Type I\*

44. PPP-T-60E, Type IV, Class I\*

45. PPP-T-66E, Type I, Class 2\*

46. Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6

47. Rule 41\*

48. SAE-AMST-23397

49. Seal Classes A, B, C

50. T-428

51. UL 181A-P/B-FX

52. UL 181B-FX

53. UL 723

54. UL Listed



## SPECIALTY GRADE DUCT

### PC 21 F

**Cargo Pit  
Cloth Duct Tape  
Flame Retardant  
Printed  
F.A.R. 25.853 Compliant**



Used in the aerospace industry to seam, seal, and repair cargo compartment liners, cover pins and rivets. Adheres well to steel, fiberglass and plastic. HVAC where building codes require a flame retardant cloth duct tape. Flame retardant and F.A.R. 25.853 tested.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	40
Thickness (mils)	13.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	23, 28, 53

### PC 623

**Nuclear Grade  
Cloth Duct Tape  
Natural Rubber Adhesive**



Used for a myriad of purposes in the construction, operation, and maintenance of nuclear power facilities. ASME NQA-1 tested.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	11.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	1, 2, 39

### PC 624

**Premium Nuclear Grade  
Cloth Duct Tape  
Natural Rubber Adhesive**



13 mil premium grade cloth tape. Used for a myriad of purposes in the construction, operation and maintenance of nuclear power facilities. ASME NQA-1 tested.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	13.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	1, 2, 39

### SF 683

**Metalized Backing  
Printed  
Natural Rubber Adhesive  
HVAC**



Designed for air-tight and moisture-free sealing, seaming and joining aluminum-backed flex ducts and sealing metal ducts. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	11.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	25, 53

### PC 857

**Printed  
Natural Rubber Adhesive  
UL 181B-FX Listed**



Used in the HVAC industry to seal, seam and join Class 1 Flex Duct. For use when the tensile strength and adhesion to stainless steel and polyethylene must meet or exceed the requirements of UL, flex duct manufacturers, and city and state building codes. UL 181B-FX listed.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	35, 52, 53

### PC 667

**Specialty Grade  
14-Day UV Resistant  
Outdoor Cloth  
Duct Tape**



Used for protective masking of non-painted surfaces of various materials such as steel, vinyl, aluminum and anodized metals. Used in plastering, stucco, concrete, pools, tile and synthetic surfaces when UV resistance is required.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	9.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

## SHURTAPE

Distributor: **Dabco Industrial Supplies**  
(800) 521-0049 - [www.dabco.ca](http://www.dabco.ca)

## VINYL COATED CLOTH

### PC 628

#### Gaffer's Tape

#### High Tack

#### Natural Rubber Adhesive



Perfectly suited for A/V, TV, photography, theatrical and motion picture industries. This weather resistant tape has good holding power for bundling wires, taping down lighting and props, and masking silk screen frames.

Tensile (lbs/in width)	46
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	12.0
Elongation (%)	5
Maximum Service Temperature (°F)	200
Applicable Specifications	—

### P-672

#### Industrial Grade

#### Solventless Rubber-based Adhesive

#### ASME NQA-1 Tested



Vinyl-coated cloth tape is waterproof and industrial strength for sealing of containers, protection from welding splatter and other temporary repairs.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	12.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 44

### P-68

#### Embossed

#### Solventless Rubber-based Adhesive

#### ASTM D5486M, ANSI N45-2-2, T-428, PM-85 Tested



Waterproof backing, high tensile strength and abrasion resistance are key features of this gaffer's tape. Also works well in book binding and color coding applications. Available in a wide range of colors.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	57
Thickness (mils)	13.5
Elongation (%)	3
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 40, 44, 50

### P-691

#### Premium Grade

#### Solventless Rubber-based Adhesive

#### ASTM D5486M, CID A-A-1586A Tested



Premium grade cloth tape performs well over a wide range of temperatures. The waterproof backing and abrasion resistance make this tape ideally suited for sealing containers and rooms.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	9, 13, 44

### P-691 NSY

#### Specialty Grade

#### Solventless Rubber-based Adhesive

#### Naval Shipyard Approved



Specialty grade tape engineered to meet the Portsmouth Naval Shipyard specification 8030-899-030J. For use wherever an extra-strong, waterproof cloth tape is needed for holding, sealing and repairing.

Tensile (lbs/in width)	69
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	1, 9, 13, 41, 44

### Lights, camera, action!

Our solventless, rubber-based, vinyl tape assures that the show will go on. It's great for bundling wires, taping props, securing lights or binding scripts. One of our grades is engineered to meet the most stringent shipyard specs and even protects from welding splatter. So when the show must go on, or the ship sails tomorrow, you can depend on Shurtape.

1 ANSI No. 45.2.2	12 CID A-A-1492B	23 FAR 25.853	34 FSI 15/SDI 25	45 PPP-T-66E, Type I, Class 2*
2 ASME NQA-1	13 CID A-A-1586A	24 FSI 0/SDI 0	35 FSI 15/SDI 30	46 Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6
3 ASTM D 1974	14 CID A-A-1671B	25 FSI 0/SDI 5	36 FSI 25/SDI 50	47 Rule 41*
4 ASTM D 5330, Type II	15 CID A-A-1684C	26 FSI 5/SDI 5	37 L-T-80B	48 SAE-AMS-T-23397
5 ASTM D 5749, Type I, Class 2	16 CID A-A-1689B, Type I, Class 2	27 FSI 5/SDI 10	38 MIL-T-23397B AMDT 2 Type II*	49 Seal Classes A, B, C
6 ASTM D 5749, Type II, Grade B	17 CID A-A-1689B, Type II	28 FSI 5/SDI 15	39 NRC Guide 1.38	50 T-428
7 ASTM D 6123/D 6123M-97	18 CID A-A-180B, Type II, Grade A	29 FSI 10/SDI 10	40 PM-85 Tested	51 UL 181A-P/B-FX
8 ASTM D 5486M-99, Type III	19 CID A-A-180B, Type II, Grade B	30 FSI 10/SDI 35	41 PNS 8030-899-030	52 UL 181B-FX
9 ASTM D 5486M-99, Type IV	20 CID A-A-55809	31 FSI 15/SDI 40	42 PPP-T-0097E, Type II, Class A*	53 UL 723
10 ASTM D 5486M-99, Type V	21 CID A-A-883B, Type I	32 FSI 11/SDI 6	43 PPP-T-42C, Type I*	54 UL Listed
11 CID A-A-113D, Type I Class A	22 CID A-A-883B, Type II	33 FSI 15/SDI 20	44 PPP-T-60E, Type IV, Class 1*	