

# MASKING & PAPER TAPES

What makes a good tape? Tensile strength? Temperature resistance? Flexibility? Solvent resistance? Or is it consistent performance, no matter what the job? Whether it's packaging, splicing, labeling, masking, or color coding, Shurtape delivers consistency, roll after roll, every time. That makes your job easier.

MASKING ADHESION SCALE	(oz./in width)
Delicate Surface	≤ 9
Low	10 - 20
Medium	21 - 25
Med-High	26 - 35
High	36 - 45
Very High	≥ 46

## GENERAL PURPOSE MASKING

### CP 106

**General Purpose  
High Adhesion  
Solventless Rubber-based  
Adhesive**



Designed for general purpose use in packaging, bundling and labeling. Offers a patented thermoplastic adhesive that allows a 100% surface contact area to the substrate with enhanced removal properties.

Tensile (lbs/in width)	18
Adhesion to Stainless Steel (oz/in width)	40
Thickness (mils)	4.8
Elongation (%)	9
Maximum Service Temperature (°F)	150
Applicable Specifications	21

The job is finished. It's right. It's dry.  
You're ready to pull tape and clean up. Shurtape doesn't splinter. It releases, and it releases you to move on to the next job... or maybe on to lunch.

### CP 101

**General Purpose  
Med-High Adhesion  
Rubber-based Adhesive**




General purpose use for bundling, packaging, holding, splicing, masking and labeling for home, school, and industry. Offers good performance and quick stick on a variety of substrates including cardboard.

Tensile (lbs/in width)	19
Adhesion to Stainless Steel (oz/in width)	34
Thickness (mils)	4.9
Elongation (%)	8
Maximum Service Temperature (°F)	150
Applicable Specifications	—

### CP 83

**Utility Grade  
Very High Adhesion  
Rubber-based Adhesive**



Designed for use in general purpose packaging, bundling, holding, splicing, tabbing and banding applications. This tape provides good adhesion, has excellent quick stick, flexibility and ease of use.

Tensile (lbs/in width)	20
Adhesion to Stainless Steel (oz/in width)	48
Thickness (mils)	5.5
Elongation (%)	8
Maximum Service Temperature (°F)	150
Applicable Specifications	—

## SHURTAPE

Distributor: Dabco Industrial Supplies  
(800) 521-0049 - [www.dabco.ca](http://www.dabco.ca)