

COLORED CREPE PAPER

CP 632



General Purpose
Med-High Adhesion
Rubber-based Adhesive



General purpose tape for use in packaging, bundling, holding, binding, splicing, labeling, color coding, banding, decorating and identification. Flexible, resistant to water, oil and solvents. Provides excellent adhesion and release from a variety of substrates.

Tensile (lbs/in width)	21
Adhesion to Stainless Steel (oz/in width)	30
Thickness (mils)	5.2
Elongation (%)	7
Maximum Service Temperature (°F)	150
Applicable Specifications	7

CP 64



Premium Grade
High Adhesion
Rubber-based Adhesive



For use on smooth substrates in applications such as packaging, bundling, holding, splicing, labeling, color coding, decorating and identification. Printable product is resistant to water and oil.

Tensile (lbs/in width)	21
Adhesion to Stainless Steel (oz/in width)	43
Thickness (mils)	6.4
Elongation (%)	9
Maximum Service Temperature (°F)	150
Applicable Specifications	—

CP 743



Opaque Black Matte
Very High Adhesion
Rubber-based Adhesive



Considered as the photographer's masking tape, its opaque black matte surface ensures light-free masking for photographic reproduction. Has good quick stick, high conformability and is hand tearable.

Tensile (lbs/in width)	21
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	6.1
Elongation (%)	7
Maximum Service Temperature (°F)	100
Applicable Specifications	—

COLORED FLATBACK PAPER

FP 227



Printable
Very High Adhesion
Rubber-based Adhesive



Printable flatback paper with clean removal adhesive properties. Well suited for full-web flexographic printing equipment or hand labeling applications.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	48
Thickness (mils)	6.1
Elongation (%)	3
Maximum Service Temperature (°F)	150
Applicable Specifications	—

FP 17



Premium Grade – Printable
High Adhesion
Rubber-based Adhesive



Premium grade printable flatback paper with an adhesive system designed to adhere well in cold temperature applications. Ideal for applications where the product will be flood-coated prior to printing.

Tensile (lbs/in width)	29
Adhesion to Stainless Steel (oz/in width)	45
Thickness (mils)	6.0
Elongation (%)	3
Maximum Service Temperature (°F)	150
Applicable Specifications	—

FP 726



Ultimate Grade – Printable
Impregnated Rope Paper
Very High Adhesion
Rubber-based Adhesive



The ultimate grade of printable flatbacks, Roped-Fiber. Designed for applications where tensile strength, printability and clean removal are critical.

Tensile (lbs/in width)	50
Adhesion to Stainless Steel (oz/in width)	65
Thickness (mils)	6.0
Elongation (%)	3
Maximum Service Temperature (°F)	150
Applicable Specifications	—

1. ANSI No. 45.2.2
2. ASME NQA-1
3. ASTM D 1974
4. ASTM D 5330, Type II
5. ASTM D 5749, Type I, Class 2
6. ASTM D 5749, Type II, Grade B
7. ASTM D 6123/D 6123M-97
8. ASTM D 5486M-99, Type III
9. ASTM D 5486M-99, Type IV
10. ASTM D 5486M-99, Type V
11. CID A-A-113D, Type I Class A

12. CID A-A-1492B
13. CID A-A-1586A
14. CID A-A-1671B
15. CID A-A-1684C
16. CID A-A-1689B, Type I, Class 2
17. CID A-A-1689B, Type II
18. CID A-A-180B, Type II, Grade A
19. CID A-A-180B, Type II, Grade B
20. CID A-A-55809
21. CID A-A-883B, Type I
22. CID A-A-883B, Type II

23. FAR 25.853
24. FSI 0/SDI 0
25. FSI 0/SDI 5
26. FSI 5/SDI 5
27. FSI 5/SDI 10
28. FSI 5/SDI 15
29. FSI 10/SDI 10
30. FSI 10/SDI 35
31. FSI 15/SDI 40
32. FSI 11/SDI 6
33. FSI 15/SDI 20

34. FSI 15/SDI 25
35. FSI 15/SDI 30
36. FSI 25/SDI 50
37. L-T-80B
38. MIL-T-23397B AMDT 2 Type II*
39. NRC Guide 1.38
40. PM-85 Tested
41. PNS 8030-899-030
42. PPP-T-0097E, Type II, Class A*
43. PPP-T-42C, Type I*
44. PPP-T-60E, Type IV, Class I*

45. PPP-T-66E, Type I, Class 2*
46. Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6
47. Rule 41*
48. SAE-AMS-T-23397
49. Seal Classes A, B, C
50. T-42B
51. UL 181A-P/B-FX
52. UL 181B-FX
53. UL 723
54. UL Listed