

EMULSION ACRYLIC CARTON SEALING

AP 101

General Purpose Grade
25 Micron Cast BOPP Film
Emulsion Acrylic Adhesive



Non-critical closure of lightweight cartons in low temperature extremes. Tough BOPP film provides flexibility and strength. Rohm and Haas adhesive offers high clarity, UV resistance, premium aging characteristics and low odor. Directly printable.

Tensile (lbs/in width)	20
Adhesion to Stainless Steel (oz/in width)	18
Thickness (mils)	1.6
Elongation (%)	120
Application Temperature Range (°F)	20 - 110
Service Temperature Range (°F)	-20 - 180
Applicable Specifications	—

AP 201

Production Grade
28 Micron Cast BOPP Film
Emulsion Acrylic Adhesive



Automated and manual sealing of light to medium weight cartons in extreme temperatures. Durable BOPP film provides stiffness and strength for automated applications. Rohm and Haas adhesive offers high clarity, UV resistance, premium aging characteristics and low odor. Directly printable.

Tensile (lbs/in width)	24
Adhesion to Stainless Steel (oz/in width)	21
Thickness (mils)	1.9
Elongation (%)	125
Application Temperature Range (°F)	20 - 110
Service Temperature Range (°F)	-20 - 180
Applicable Specifications	—

AP 301

Performance Grade
35 Micron Cast BOPP Film
Emulsion Acrylic Adhesive



Automated carton sealing of light to medium weight cartons subjected to handling stress. Durable BOPP film and quick-bonding Rohm and Haas adhesive provide excellent quick stick and superior clarity. For a wide range of applications, environments and temperatures. Directly printable.

Tensile (lbs/in width)	24
Adhesion to Stainless Steel (oz/in width)	23
Thickness (mils)	2.2
Elongation (%)	125
Application Temperature Range (°F)	20 - 110
Service Temperature Range (°F)	-20 - 180
Applicable Specifications	15

AP 401

High Performance Grade
40 Micron Cast BOPP Film
Emulsion Acrylic Adhesive



Heavy duty manual and automated carton sealing under rough handling and load stress. Critical closure of bulky packages. Rohm and Haas adhesive provides excellent quick stick and superior clarity. For a wide range of applications, environments and temperatures. Directly printable.

Tensile (lbs/in width)	33
Adhesion to Stainless Steel (oz/in width)	25
Thickness (mils)	2.5
Elongation (%)	140
Application Temperature Range (°F)	20 - 110
Service Temperature Range (°F)	-20 - 180
Applicable Specifications	15

Once your cartons leave your loading dock, who knows what they're in for? Temperature extremes. Clogged conveyor belts. Splashes. Drops. Our full line of carton sealing tapes can assure your cartons get there intact, with a strong seal.

AP SERIES

Use AP Series for sealing in temperature extremes and for UV protection.

PRINTED SERIES

Protect your package with security prints or place your custom artwork on our carton sealing tapes.

PP SERIES

Use PP Series to seal high-end graphic cartons where clarity is a must.

SHURTAPE

Distributor: Dabco Industrial Supplies
 (800) 521-0049 - www.dabco.ca