

## PRINTED CARTON SEALING

### HP 240

**Production Grade**  
**30 Micron Cast BOPP Film**  
**Standard Prints**



Printed stock messages prevent pilferage and inform handlers of care. Same consistent strength and hold as HP 200. Available prints: STOP if Seal is Broken Or Package Damaged Check Contents Before Signing Receipt; FRAGILE HANDLE WITH CARE.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	44
Thickness (mils)	1.9
Elongation (%)	130
Holding Power to Fiberboard (min)	10,000
Application Temperature Range (°F)	35 – 110
Service Temperature Range (°F)	20 – 150
Applicable Specifications	3, 15

### HP 250

**Production Grade**  
**30 Micron Cast BOPP Film**  
**Custom Prints**



This packaging tape can be custom printed with your own message. Prevents pilferage and allows personalization of all outgoing cartons. Great way to reinforce your point of view. Lead time and minimum orders apply.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	44
Thickness (mils)	1.9
Elongation (%)	130
Holding Power to Fiberboard (min)	10,000
Application Temperature Range (°F)	35 – 110
Service Temperature Range (°F)	20 – 150
Applicable Specifications	3, 15

### WP 240

**Production Grade**  
**Custom Printed**  
**Reinforced Paper Tape**



Reinforced kraft paper water activated tape complete with custom printed message allows for delivery of goods without pilferage. Lead time and minimum orders apply.

Top Sheet (lbs)	24
Bottom Sheet (lbs)	24
MD Pattern	1-1-1
MD Spacing (in)	5/8
MD Tensile (lbs/in width)	52
CD Tensile (lbs/in width)	30
CD Spacing (in)	1.25
Applicable Specifications	47

## SOLVENT-BASED ACRYLIC CARTON SEALING

### PP 802

**Premium Grade**  
**25 Micron Cast BOPP Film**  
**Solvent-based Acrylic Adhesive**



Use with hand or machine dispenser to seal, repair, and bundle corrugated cartons, paper or film containers. Excellent initial tack, high holding power and wide temperature range.

Tensile (lbs/in width)	16
Adhesion to Stainless Steel (oz/in width)	25
Thickness (mils)	2.0
Elongation (%)	140
Application Temperature Range (°F)	20 – 110
Service Temperature Range (°F)	-20 – 180
Applicable Specifications	—

### PP 810

**Premium Grade**  
**25 Micron Cast BOPP Film**  
**Solvent-based Acrylic Adhesive**



Light to medium carton sealing applications in a wide range of temperatures and normal shipping and handling environments. Usable with hand dispensers.

Tensile (lbs/in width)	16
Adhesion to Stainless Steel (oz/in width)	22
Thickness (mils)	1.8
Elongation (%)	140
Application Temperature Range (°F)	20 – 110
Service Temperature Range (°F)	-20 – 180
Applicable Specifications	—

### PP 815

**Heavy Duty Grade**  
**40 Micron Cast BOPP Film**  
**Solvent-based Acrylic Adhesive**



Critical sealing and repairing of corrugated containers in hot or cold environments. Usable with hand dispenser.

Tensile (lbs/in width)	26
Adhesion to Stainless Steel (oz/in width)	28
Thickness (mils)	2.6
Elongation (%)	150
Application Temperature Range (°F)	20 – 110
Service Temperature Range (°F)	-20 – 180
Applicable Specifications	—

1 ANSI No. 45.2.2

2 ASME NQA-1

3 ASTM D 1974

4 ASTM D 5330, Type II

5 ASTM D 5749, Type I, Class 2

6 ASTM D 5749, Type II, Grade B

7 ASTM D 6123/D 6123M-97

8 ASTM D 5486M-99, Type III

9 ASTM D 5486M-99, Type IV

10 ASTM D 5486M-99, Type V

11 CID A-A-113D, Type I Class A

12 CID A-A 1492B

13 CID A-A-1586A

14 CID A-A-1671B

15 CID A-A-1684C

16 CID A-A-1689B, Type I, Class 2

17 CID A-A-1689B, Type II

18 CID A-A-180B, Type II, Grade A

19 CID A-A-180B, Type II, Grade B

20 CID A-A-55809

21 CID A-A-883B, Type I

22 CID A-A-883B, Type II

23 FAR 25.853

24 FSI 0/SDI 0

25 FSI 0/SDI 5

26 FSI 5/SDI 5

27 FSI 5/SDI 10

28 FSI 5/SDI 15

29 FSI 10/SDI 10

30 FSI 10/SDI 35

31 FSI 15/SDI 40

32 FSI 11/SDI 6

33 FSI 15/SDI 20

34 FSI 15/SDI 25

35 FSI 15/SDI 30

36 FSI 25/SDI 50

37 L-T-80B

38 MIL-T-23397B AMDT 2 Type II\*

39 NRC Guide 1.38

40 PM-85 Tested

41 PNS 8030-899-030

42 PPP-T-0097E, Type II, Class A\*

43 PPP-T-42C, Type I\*

44 PPP-T-60E, Type IV, Class I\*

45 PPP-T-66E, Type I, Class 2\*

46 Pressure Classes SMACNA

1/2, 1, 2, 3, 4, & 6

47 Rule 41\*

48 SAE-AMS-T-23397

49 Seal Classes A, B, C

50 T-428

51 UL 181A-P/B-FX

52 UL 181B-FX

53 UL 723

54 UL Listed