

FILAMENT STRAPPING

GS 490

Economy Grade

Cast Polypropylene Film
Synthetic Rubber/Resin
Hot Melt Adhesive
Fiberglass Reinforced



For general purpose strapping, packaging, bundling and palletizing. Resistant to moisture and solvents. Aggressive, synthetic rubber/resin adhesive for quick stick, shock resistance and high shear strength. Backing resists splitting and cracking.

Tensile (lbs/in width)	100
Adhesion to Stainless Steel (oz/in width)	72
Thickness (mils)	4.8
Elongation (%)	5
Maximum Service Temperature (°F)	150
Applicable Specifications	—

GS 500

Utility Grade

Cast Polypropylene Film
Synthetic Rubber/Resin
Hot Melt Adhesive
Fiberglass Reinforced



Light duty strapping, packaging, bundling and palletizing. Resists moisture and solvents. Good adhesion, quick stick and shock resistance. Backing resists splitting and cracking.

Tensile (lbs/in width)	150
Adhesion to Stainless Steel (oz/in width)	80
Thickness (mils)	5.4
Elongation (%)	3.7
Maximum Service Temperature (°F)	150
Applicable Specifications	—

GS 501

Industrial Grade

Cast Polypropylene Film
Synthetic Rubber/Resin
Hot Melt Adhesive
Fiberglass Reinforced



Medium duty strapping, packaging, bundling and palletizing. Resistant to moisture and solvents. Excellent adhesion and aggressive tack. Backing resists splitting and cracking. Large diameter filament for added tensile strength.

Tensile (lbs/in width)	175
Adhesion to Stainless Steel (oz/in width)	75
Thickness (mils)	5.4
Elongation (%)	3.7
Maximum Service Temperature (°F)	150
Applicable Specifications	—

GS 521

High Performance Grade

Cast Polypropylene Film
Synthetic Rubber/Resin
Hot Melt Adhesive
Fiberglass Reinforced



High tensile strength for maximum security. Heavy duty closing, strapping, packaging, bundling, unitizing and palletizing and L-Clip applications. Excellent adhesion and aggressive tack. Backing resists splitting and cracking.

Tensile (lbs/in width)	300
Adhesion to Stainless Steel (oz/in width)	70
Thickness (mils)	6.6
Elongation (%)	3.6
Maximum Service Temperature (°F)	150
Applicable Specifications	4, 42

GS 531

Premium Grade

Cast Polyester Film
Synthetic Rubber/Resin
Hot Melt Adhesive
Fiberglass Reinforced



Maximum security tape for heavy duty closing, strapping, packaging, protecting, bundling, reinforcing, sealing, unitizing, palletizing and L-clip applications.

Tensile (lbs/in width)	325
Adhesion to Stainless Steel (oz/in width)	70
Thickness (mils)	6.7
Elongation (%)	4
Maximum Service Temperature (°F)	150
Applicable Specifications	4, 42

Pallets should stay palletized.

Bundles should stay bundled.

Shurtape strapping tapes are strong

enough to stick, tough enough

to stay and durable enough

to protect – for a trip across

the floor or across the ocean.

SHURTAPE INC

Distributor: **Dabco Industrial Supplies**
(800) 521-0049 - www.dabco.ca