

CLOTH & DUCT TAPES

Whatever your industry – HVAC, automotive, agriculture, aviation, construction, entertainment, even nuclear – you'll find the best tape for your next job right here. Our comprehensive line of duct and cloth tapes is engineered to exacting specs. We've virtually eliminated de-lamination and film variability. No other line of cloth and duct tapes performs better than Shurtape. We make your job, and your life, easier.

Suitable for a wide variety of applications, Shurtape co-extruded utility tape is a terrific general purpose tape for everything from packaging, holding and sealing to seaming, bundling and repairing. We have grades that meet UL 723, a requirement for specialized jobs.

CO-EXTRUDED DUCT

PC 590

**Co-extruded
Waterproof Backing
Natural Rubber Adhesive**



For general use in packaging, bundling, sealing, seaming, repairing, holding and waterproofing. Good adhesion characteristics.

Tensile (lbs/in width)	20
Adhesion to Stainless Steel (oz/in width)	45
Thickness (mils)	7.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	—

PC 595

**Co-extruded
Waterproof Backing
Natural Rubber Adhesive**



Excellent for non-critical, general purpose packaging, bundling, sealing, seaming, repairing and holding. Meets requirements of UL 723.

Tensile (lbs/in width)	20
Adhesion to Stainless Steel (oz/in width)	45
Thickness (mils)	8.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	26, 53

PC 600

**Polycoated
High Tack Adhesive
Natural Rubber
Adhesive
Co-extruded**



General purpose use in industrial, plumbing, carpet, color coding, splicing, and other home and general repairs.

Tensile (lbs/in width)	22
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	9.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	—

PC 618

**Light Industrial Grade
Poly Cotton Cloth Duct Tape
Natural Rubber
Adhesive
Co-extruded**



To seal cartons, bind books, repair seats, bundle wires, color code, splice, repair, seal hatch covers and cargo doors in the shipping industry. Use as a condensation barrier in appliance assemblies. Meets requirements of UL 723.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	10.0
Elongation (%)	15
Maximum Service Temperature (°F)	200
Applicable Specifications	34, 53

SHURTAPE

Distributor: Dabco Industrial Supplies
(800) 521-0049 - www.dabco.ca