

PERFORMANCE GRADE DUCT

PC 622

**Premium Grade
Cloth Duct Tape**
Stucco Application
Natural Rubber Adhesive



12.5 mil premium grade cloth duct tape used for protection of window and door frames during stucco application; high performance motorsports applications, and heavy duty bundling, holding, and splicing. Meets requirements of UL 723.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	55
Thickness (mils)	12.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	29, 53

PC 625

Military Grade
Lusterless
Natural Rubber Adhesive
ASTM 5486 Tested



Used for packaging, sealing, bundling and stage preparation. High performance, polyethylene coated, waterproof packaging tape that meets government specifications. ASTM 5486 tested.

Tensile (lbs/in width)	40
Adhesion to Stainless Steel (oz/in width)	50
Thickness (mils)	12.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	9, 44

PC 657

Premium Grade
Co-extruded Quality
Natural Rubber Adhesive



Used in high performance motor sports applications, pre-manufactured housing and RV assembly, critical industrial applications, and for protection during metal peening operations. Meets requirements of UL 723.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	60
Thickness (mils)	14.5
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	31, 53

PC 658

Super Bottom Board Tape
Co-extruded Cloth
Duct Tape
Natural Rubber Adhesive



Used for seaming and sealing bottom board materials in pre-manufactured homes and RVs during assembly, set-up, and maintenance. Also used for protection of surfaces in metal peening operations. Meets requirements of UL 723.

Tensile (lbs/in width)	30
Adhesion to Stainless Steel (oz/in width)	85
Thickness (mils)	17.0
Elongation (%)	10
Maximum Service Temperature (°F)	200
Applicable Specifications	33, 53

P-670

Book Binding, HVAC
Co-extruded
Solventless Rubber
Based Adhesive
Rocketdyne RB0195-002
Listed



Used for sealing and seaming applications in the HVAC industry. Other applications include protection, splicing, bundling and holding. Conformable, waterproof and Rocketdyne RB0195-002 tested.

Tensile (lbs/in width)	38
Adhesion to Stainless Steel (oz/in width)	95
Thickness (mils)	11.0
Elongation (%)	4
Maximum Service Temperature (°F)	—
Applicable Specifications	—

P-69

The Original Duct Tape
Co-extruded
Solventless Rubber-based
Adhesive
ASTM D5486M
CID A-A-1586A Tested



Used for waterproof sealing of containers and ductwork. Other applications include protection, splicing, bundling and holding in the aerospace industry. Highly conformable and waterproof.

Tensile (lbs/in width)	43
Adhesion to Stainless Steel (oz/in width)	134
Thickness (mils)	12.0
Elongation (%)	3
Maximum Service Temperature (°F)	—
Applicable Specifications	9, 13

1. ANSI No. 45.2.2

2. ASME NQA-1

3. ASTM D 1974

4. ASTM D 5330, Type II

5. ASTM D 5749, Type I, Class 2

6. ASTM D 5749, Type II, Grade B

7. ASTM D 6123/D 6123M-97

8. ASTM D 5486M-99, Type III

9. ASTM D 5486M-99, Type IV

10. ASTM D 5486M-99, Type V

11. CID A-A-113D, Type I Class A

12. CID A-A-1492B

13. CID A-A-1586A

14. CID A-A-1671B

15. CID A-A-1684C

16. CID A-A-1689B, Type I, Class 2

17. CID A-A-1689B, Type II

18. CID A-A-180B, Type II, Grade A

19. CID A-A-180B, Type II, Grade B

20. CID A-A-55809

21. CID A-A-883B, Type I

22. CID A-A-883B, Type II

23. FAR 25.853

24. FSI 0/SDI 0

25. FSI 0/SDI 5

26. FSI 5/SDI 5

27. FSI 5/SDI 10

28. FSI 5/SDI 15

29. FSI 10/SDI 10

30. FSI 10/SDI 35

31. FSI 15/SDI 40

32. FSI 11/SDI 6

33. FSI 15/SDI 20

34. FSI 15/SDI 25

35. FSI 15/SDI 30

36. FSI 25/SDI 50

37. L-T-80B

38. MIL-T-23397B AMDT 2 Type II*

39. NRC Guide 1.38

40. PM-85 Tested

41. PNS 8030-899-030

42. PPP-T-0097E, Type II, Class A*

43. PPP-T-42C, Type I*

44. PPP-T-60E, Type IV, Class I*

45. PPP-T-66E, Type I, Class 2*

46. Pressure Classes SMACNA 1/2, 1, 2, 3, 4, & 6

47. Rule 41*

48. SAE-AMST-23397

49. Seal Classes A, B, C

50. T-428

51. UL 181A-P/B-FX

52. UL 181B-FX

53. UL 723

54. UL Listed