

DOUBLE-COATED TAPES

The trade show doors open in 30 minutes. Your client's exhibit was finished late, shipped late and arrived late. Now their booth has to be set up in time for the show. Shurtape double-coated tape attaches the carpet to the convention floor, anchors illustrations to the exhibit wall, mounts photographs on an easel, and basically, saves the day. Don't forget that carpet seam waiting to trip up a buyer. Whether your job requires mounting, splicing, laminating, or joining, Shurtape does the job.

DOUBLE-COATED PAPER

DF 63

General Purpose
Double-faced
Crepe Paper
Rubber-based Adhesive



Mounting, holding, splicing, tabbing and fastening a variety of substrates. Durability, good tensile strength. Superior adhesion to a variety of substrates. Features white, siliconized crepe paper liner. Both tape and release liner are wrinkle-resistant.

Tensile (lbs/in width)	23
Adhesion to Stainless Steel (oz/in width)	29
Thickness (mils)	6.4
Elongation (%)	9
Maximum Service Temperature (°F)	225
Applicable Specifications	18

DF 65

General Purpose
Double-faced
Flat Paper
Aggressive
Rubber-based Adhesive



Mounting, holding, splicing, tabbing and fastening a variety of substrates. Good tensile strength and durability. Superior, aggressive adhesion to a variety of substrates. Features white, siliconized flat paper liner. Both tape and release liner are wrinkle-resistant.

Tensile (lbs/in width)	27
Adhesion to Stainless Steel (oz/in width)	66
Thickness (mils)	4.8
Elongation (%)	2
Maximum Service Temperature (°F)	225
Applicable Specifications	19

DT 100

Double-faced
Non-woven Tissue
Solvent-based Acrylic
Adhesive



Possessing high shear strength and excellent conformability, DT 100 is ideal for splicing of corrugated board, paper, plastics and other continuous web processes. Perfect for mounting and laminating irregular shaped metals, foams, foils and nameplates.

Tensile (lbs/in width)	4.5
Adhesion to Stainless Steel (oz/in width)	65
Thickness (mils, without liner)	4.0
Elongation (%)	5
Maximum Service Temperature (°F)	—
Applicable Specifications	—

GG 200

General Purpose
Double-faced
Rubber-based Adhesive



Factory and clubhouse golf grip installation. Mounting, holding, splicing, tabbing and fastening a variety of substrates for which an aggressive, double-faced tape is needed. Superior adhesion to graphite, steel and titanium. Constructed with a siliconized crepe paper liner.

Tensile (lbs/in width)	20
Adhesion to Stainless Steel (oz/in width)	48
Thickness (mils)	6.4
Elongation (%)	9
Maximum Service Temperature (°F)	150
Applicable Specifications	—

SHURTAPE

Distributor: **Dabco Industrial Supplies**
 (800) 521-0049 - www.dabco.ca